



R770

Product Description

Features

R770 is a two-component polyurethane parquet adhesive which follows DIN 281 and does not contain water or organic solvents. The adhesive hardens by a chemical reaction without shrinking. R770 is especially suitable for timbers extremely sensitive to swelling and for low / non-absorbent substrates. It may also be used for the full area bonding of laminated floor coverings.

- Water and solvent free
- No swelling of the wood
- Excellent adhesion to almost all substrates and timber materials
- Firm texture – retains trowel pattern
- Good open time

Technical Data

Product type:	Mixture of Polyols and MDI
Colour:	Component A: white, Component B: brown
Viscosity:	Easy to apply - stable
Density:	1.5 g/cm ³
Cleaning agents:	S100, acetone and ethanol. Hardened adhesive can only be removed mechanically.
Storage / transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport. Store in a dry, well ventilated place.
Shelf life:	6 months.
Pack size:	6 kg buckets (90 per pallet)

Safety

Harmful (component B).

Component B contains Diphenylmethane-4,4'-diisocyanate (Isomers, Homologue). Harmful. Damaging to health when inhaled. Irritates eyes, respiratory organs and skin. Do not inhale fumes. Wear appropriate protective clothing, gloves, goggles and facial mask. Change contaminated clothes immediately. In case of eye contact rinse with lots of water – consult a physician immediately. In case of skin contact clean with plenty of water and soap. In case of accident or sickness consult a physician, if possible show information sheet or label.

Additional detailed information is noted in the appropriate Safety Data Sheet.