

SAFETY DATA SHEET

2 PART WOOD FILLER - HARDENER

Page 1 Issued: 15/2/10 Revision No: 3

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product name:2 PART WOOD FILLER - HARDENERProduct code:WOODHPCATCompany name:EVERBUILD BUILDING PRODUCTS LTD
SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND
Tel: 0044 113 240 3456
Fax: 0044 113 240 0024
Emergency tel: 0044 113 240 3456 (office hours only)
Email: pault@everbuild.co.uk

2. HAZARDS IDENTIFICATION

Classification under CHIP:	May cause fire. Irritating to eyes. May cause sensitisation by skin contact.	
Workplace exposure limit:	This substance does not have a workplace exposure limit.	
PBT:	This substance is not identified as a PBT substance.	
Directive 1999/45/EC:	This mixture meets the criteria for classification as dangerous in accordance	
	with Directive 1999/45/EC.	

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: DIBENZOYL PEROXIDE 30-50% EINECS: 202-327-6 CAS: 94-36-0 [E] R3; [O] R7; [Xi] R36; [Sens.] R43

4. FIRST AID MEASURES

Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to	
	skin. Wash immediately with plenty of soap and water. Consult a doctor.	
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.	
Ingestion:	Wash out mouth with water. Consult a doctor.	
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so.	
	Consult a doctor.	

5. FIRE-FIGHTING MEASURES

Extinguishing media:	Suitable extinguishing media for the surrounding fire should be used.	
Exposure hazards:	In combustion emits toxic fumes.	
Protection of fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent	
	contact with skin and eyes.	

Issued: 15/2/10

SAFETY DATA SHEET

2 PART WOOD FILLER - HARDENER

6. ACCIDENTAL RELEA	SE MEASURES
Personal precautions:	Do not attempt to take action without suitable protective clothing - see
	section 8 of SDS. Do not create dust.
Environmental precautions:	Do not discharge into drains or rivers.
Clean-up procedures:	Transfer to a closable, labelled salvage container for disposal by an
	appropriate method.
7. HANDLING AND STO	RAGE
Handling requirements:	Avoid direct contact with the substance. Do not handle in a confined space.
	Ensure there is sufficient ventilation of the area.
Storage conditions:	Store in cool, well ventilated area. Keep container tightly closed. Keep away
	from sources of ignition.
Suitable packaging:	Must only be kept in original packaging.
8. EXPOSURE CONTRO	LS / PERSONAL PROTECTION
Hazardous ingredients:	DIBENZOYL PEROXIDE
	UK - 8 hour TWA: 5 mg/m3
Engineering measures:	Ensure there is sufficient ventilation of the area.
Respiratory protection:	Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour
	concentration is above OES or if ventilation is poor Self-contained breathing
	apparatus must be available in case of emergency.
Hand protection:	Protective gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State:	Paste
Colour:	White
Odour:	Pleasant
Evaporation rate:	Moderate
Oxidising:	Oxidising (by EC criteria)
Solubility in water:	Slightly soluble
Also soluble in:	Most organic solvents.
Viscosity:	Viscous
Autoflammability°C:	>380
Relative density:	1.14-1.17
pH:	slightly acidic

Issued: 15/2/10

SAFETY DATA SHEET

2 PART WOOD FILLER - HARDENER

Page 3

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Reducing agents. Acids. Bases. Metals.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute effects: Irritating to eyes.Sensitisation: May cause sensitisation by skin contact.

11. TOXICOLOGICAL INFORMATION (SYMPTOMS)

Skin contact:There may be irritation and redness at the site of contact.Eye contact:There may be irritation and redness. The eyes may water profusely.Ingestion:There may be soreness and redness of the mouth and throat.Inhalation:Exposure may cause coughing or wheezing.

12. ECOLOGICAL INFORMATION

Persistence and degradability: Biodegradable.

Bioaccumulative potential:	No bioaccumulation potential.
Other adverse effects:	Negligible ecotoxicity.
PBT identification:	This substance is not identified as a PBT substance.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Dispose of according to local or national legislation

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no:	3108	ADR Class:	5.2
Packing group:	II	Classification code:	P1
Shipping name:	ORGANIC PEROXIDE, TYPE E, SOLID		
Labelling:	5.2		
	DRUG REPERCINE 5.2		
IMDG / IMO			

UN no: 3108 Packing group: II

SAFETY DATA SHEET

2 PART WOOD FILLER - HARDENER

Page 4

Marine pollutant:	NO Labelling:	5.2		
IATA / ICAO				
UN no:	3108 Class:	52		
Packing group:		510(P&CA); 513(PAO)		
Labelling:	_			
_				
15. REGULATORY INFO				
Hazard symbols:				
	Oxidising.			
Risk phrases:	R7: May cause fire.			
	R36: Irritating to eyes.			
	R43: May cause sensitisation by skin contact.			
Safety phrases:	S2: Keep out of the reach of children.			
	S36/37/39: Wear suitable protective clothing, gloves and eye / face			
	protection.			
	S17: Keep away from combustible material.			
	S24/25: Avoid contact with skin and eyes.			
	S46: If swallowed, seek medical advice immediately and show this container			
	or label.			
Haz. ingredients (label):	DIBENZOYL PEROXIDE			
Note:	The regulatory information given above only indicates the principal			
	regulations specifically applicable to the product described in the safety data			
	sheet. The user's attention is drawn to the possible existence of additional			
	provisions which complete these regulations. Refer to all applicable national,			
	international and local regulations or provisions.			
16. OTHER INFORMATIC	DN			
Other information:	This safety data sheet is prepared in accordance with Regulation (E	C) No		
	1907/2006.			
	* indicates text in the SDS which has changed since the last revision	٦.		
Risk phrases used in s.3:	R3: Extreme risk of explosion by shock, friction, fire or other source	s of		
	ignition.			
	R7: May cause fire.			
	R36: Irritating to eyes.			
	R43: May cause sensitisation by skin contact.			
Legal disclaimer:	The above information is believed to be correct but does not purpor	t to be all		

SAFETY DATA SHEET

2 PART WOOD FILLER - HARDENER

Page 5

inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.