



# SAFETY DATA SHEET

Page 1 of 4

## Fiddes Liquid Floor Wax

Revision 0  
Revision date

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

**Product name** Fiddes Liquid Floor Wax  
**Company** Fiddes & Son Ltd  
Florence Works, Brindley Road, Cardiff, South Glamorgan, CF11 8TX  
info@fiddes.co.uk  
www.fiddes.co.uk  
**Telephone** +44 (0)29 2034 0323  
**Fax** +44 (0)29 2034 3235

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

#### Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
White spirit	40 - 50%	64742-82-1	265-185-4	Xn; R65 N; R51/53 R10-66
n-Hexane	1 - 10%	110-54-3	203-777-6	F; R11 Repr Cat 3; R62 Xn; R65-48/20 Xi; R38 R67 N; R51/53
Cyclohexane	1 - 10%	110-82-7	203-806-2	F; R11 Xn; R65 Xi; R38 R67 N; R50/53
Methylcyclohexane	1 - 10%	108-87-2	203-624-3	F; R11 Xn; R65 Xi; R38 R67 N; R51/53
Naphtha (petroleum), hydrotreated light	20 - 30%	64742 49-0		N;R51/53 Xn;R65

### 3. HAZARDS IDENTIFICATION

**Main hazards** Flammable Harmful: danger of serious damage to health by prolonged exposure through inhalation. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Possible risk of impaired fertility. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

**Other hazards** In use, may form flammable/explosive vapour-air mixture.

### 4. FIRST AID MEASURES

**Skin contact** Wash off immediately with plenty of soap and water. Remove contaminated clothing.

**Eye contact** Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.

**Inhalation** Move the exposed person to fresh air. Seek medical attention.

**Ingestion** DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water. Seek medical attention.

**General information** If you feel unwell, seek medical advice (show the label where possible). Keep the affected person warm and at rest. Remove contaminated clothing. Wash all contaminated clothing before reuse.

### 5. FIRE FIGHTING MEASURES

**Extinguishing media** Use extinguishing media appropriate to the surrounding fire conditions.

**Fire hazards** Burning produces irritating, toxic and obnoxious fumes.

**Protective equipment** Wear: Self-contained breathing apparatus.

# Fiddes Liquid Floor Wax

Revision  
Revision date

0

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions</b>	Ensure adequate ventilation of the working area. Keep personnel away from spill. Evacuate personnel to a safe area.
<b>Environmental precautions</b>	Do not allow product to enter drains.
<b>Clean up methods</b>	Clean spillage area thoroughly with plenty of water. Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal.

## 7. HANDLING AND STORAGE

<b>Handling</b>	Wear suitable protective equipment. Do not breathe gas/fumes/vapour/spray. Use in a well ventilated area.
<b>Storage</b>	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure limits

n-Hexane	WEL 8-hr limit ppm: 20 WEL 15 min limit ppm: -	WEL 8-hr limit mg/m3: 72 WEL 15 min limit mg/m3: -
Cyclohexane	WEL 8-hr limit ppm: 100 WEL 15 min limit ppm: 300	WEL 8-hr limit mg/m3: 350 WEL 15 min limit mg/m3: 1050

<b>Engineering measures</b>	Ensure adequate ventilation of the working area.
<b>Respiratory protection</b>	Wear: Suitable respiratory equipment. Self-contained breathing apparatus.
<b>Hand protection</b>	Chemical resistant gloves (PVC)
<b>Eye protection</b>	Approved safety goggles. Avoid contact with eyes.
<b>Protective equipment</b>	Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing. Apron (Plastic or rubber) Rubber boots.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Description</b>	Liquid.
<b>Colour</b>	Amber.
<b>Odour</b>	Characteristic.
<b>Flash point</b>	23°C
<b>Water solubility</b>	Immiscible in water. Insoluble in water.

## 10. STABILITY AND REACTIVITY

<b>Stability</b>	Stable under normal conditions.
<b>Conditions to avoid</b>	Heat, sparks and open flames.
<b>Materials to avoid</b>	Oxidising agents.
<b>Hazardous decomposition products</b>	None.

## 11. TOXICOLOGICAL INFORMATION

<b>Acute toxicity</b>	Harmful if swallowed.
<b>Corrosivity</b>	May cause irritation to skin.
<b>Repeated or prolonged exposure</b>	Prolonged or repeated exposure may cause irritation to skin and mucous membranes.

## 12. ECOLOGICAL INFORMATION

<b>Ecotoxicity</b>	No data is available on this product.
--------------------	---------------------------------------

# Fiddes Liquid Floor Wax

Revision 0  
Revision date

## 13. DISPOSAL CONSIDERATIONS

<b>General information</b>	Can be incinerated if in compliance with local and national regulations. Dispose of in compliance with all local and national regulations.
<b>Disposal of packaging</b>	Empty containers can be sent for disposal or recycling.

## 14. TRANSPORT INFORMATION

### ADR/RID

UN 1263	Packing group III
Class 3	Hazard ID 33
Proper Shipping Name PAINT .	

### IMDG

UN 1263	Packing group III
Class 3	Marine pollutant .
EmS Code F-E S-E	

### IATA

UN 1263	Packing group III
Class 3	Subsidiary risk -
Packing Instruction 310 (Cargo)	Maximum quantity 220 L
Packing Instruction 309 (Passenger)	Maximum quantity 60 L

## 15. REGULATORY INFORMATION

**Labelling** The product is classified in accordance with 67/548/EEC.

**Symbols** Xn - Harmful; N - Dangerous for the environment



**Risk phrases**

R10 - Flammable.  
R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R62 - Possible risk of impaired fertility.  
R65 - Harmful: may cause lung damage if swallowed.  
R66 - Repeated exposure may cause skin dryness or cracking.

**Safety phrases**

S29 - Do not empty into drains.  
S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

# Fiddes Liquid Floor Wax

Revision 0  
Revision date

## 16. OTHER INFORMATION

### Text of risk phrases in Section 2

R10 - Flammable.  
R11 - Highly flammable.  
R38 - Irritating to skin.  
R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R62 - Possible risk of impaired fertility.  
R65 - Harmful: may cause lung damage if swallowed.  
R66 - Repeated exposure may cause skin dryness or cracking.  
R67 - Vapours may cause drowsiness and dizziness.

### Revision

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.