

Protector Satin



Slip resistant



Odourless



Specially formulated to maintain high-traffic varnished wood floors with satin or gloss finish



Suitable for wood floors* and plastic flooring



PRODUCT DESCRIPTION

- Based on a new formulation, combining the hardness of metallised acrylic resins with the flexibility of polyethylene waxes, **Blanchon Protector Satin** provides long-lasting protection and beauty to varnished wood floors (and plastic flooring).
- Thanks to extremely minute components, **Protector Satin** fills the wood pores preventing dirt build-up and forms an even coating with outstanding wear resistance. No buffing required.
- Thanks to the high stability of its copolymer ingredients, **Protector Satin** is non-yellowing and non-flaking.
- **Protector Satin** gives a slip-resistant finish.
- With its specific adhesive properties, **Protector Satin** is the key element in providing a protective coat on varnished wood floors (protecting wood floors which are subject to heavy traffic).
- **Protector Satin** is compatible with most types of wood floor lacquers.
- **Protector Satin** is a white liquid which becomes completely transparent on drying.

SURFACE PREPARATION

- * **Protector Satin** can be applied over all silicone-free wood floor lacquers with a satin or gloss finish after suitable preparation.
- Before applying, the floor lacquer must have dried and hardened for at least 10 days.
- It is essential to damp-clean⁽¹⁾ the surface before it is treated using 0.5 L of Blanchon Remover diluted in 10 L of water. The floor should then be rinsed with a damp cloth⁽¹⁾.
- Apply Protector Satin onto a clean, dry, grease-free surface.

IMPORTANT: on pre-varnished wood floors which can be very hygroscopic (beech, etc.), first test on an inconspicuous area.

⁽¹⁾ A wood floor should never get too wet. Use a damp mop or cloth, never a soaking wet one.

DIRECTIONS FOR USE

- Apply 1 or 2 coats of Protector Satin using a sponge mop, a micro-fiber mop dust mop (Faubert) or floorcloth.
- Wait 1 hour between each coat to allow for in-depth polymerisation.

Cleaning of tools

- Rinse thoroughly with water immediately after use.
- Protect the environment:
 - Wring the tools properly and wipe them dry immediately after use.
 - Wash them in a dish with a small amount of water. Leave the used water to evaporate.
 - The accumulated dry sediments can be disposed of with trash.
 - Tightly close the container after use.
 - Return the empty container for recycling.
 - Please contact the local authorities for information on the collection and disposal of wastes.
 - Do not pour liquid wastes into sewer systems.

DRYING TIMES

- Dust-free: 15 minutes.
- Before recoating: 1 hour under normal conditions.
- Return to use: after 1h30.

Blanchon

Protector Satin

COVERAGE

- Around 40 to 50 m² per litre per coat.

MAINTENANCE

- Damp-clean with Blanchon Cleaner Lisabril™ (followed, if required, by a light buffing with a beige or white pad).
- Routine cleaning: use a vacuum cleaner, broom or lamb's wool cloth. Occasionally, damp-clean using a well wrung out cloth or mop (never a soaking wet one) using Cleaner Lisabril™. Do not use abrasive detergents or products containing ammonia or silicone.
- Maintenance can be alternated with Blanchon Maintenance.
- **Protector Satin** can be applied over itself: occasionally, apply a thin coat to give a perfect finish.

NB: Cleaner Lisabril™ can be sprayed on: dilute at 20% in water and use a buffing machine fitted with a red pad.

TECHNICAL DATA

USE	Protection and renovation of varnished wood floors and plastic flooring
RESIN TYPE	Metal-complex acrylics
AFNOR CLASSIFICATION	Family 1, class 5b
DENSITY	1.027 (at 20°C, as per NF T 30020)
FLUIDITY	30 seconds (ISO Cup n° 2.5 at 20°C)
REGULATORY INFORMATION	Refer to the relevant Safety Data Sheet (also available on www.blanchon.com or www.quickfds.com)
PH	8.5
BEFORE RECOATING	1 hour
SCRATCH RESISTANCE	6H pencil
RESISTANCE TO HOUSEHOLD PRODUCTS	Protector Satin is sensitive to alkaline detergents Use Blanchon Daily Cleaner instead of alkaline cleaning products
STORAGE	Protect from frost (be careful of storing in vehicles)

Technical Data Sheet issued on the 05.2015
The information provided in this Technical Data Sheet is given in good faith for information purposes only. In no case whatsoever can this information be considered as a guarantee given by us nor engage our responsibility when our products are used. Since we are constantly striving to improve our products, the information given here may be subject to modification without prior notice.
This Technical Data Sheet cancels and supersedes all previous versions.

28 rue Charles Martin - BP 105
69192 SAINT-FONS CEDEX - FRANCE Tél. 04 72 89 06 00 - Fax 04
78 70 07 18
Export Lines: Tel: (0033) 472 89 06 09
Fax: (0033) 472 89 06 02



BLANCHON S.A. - Est. 1832 - A stock company with a board of directors and a supervisory board,
with a registered capital of 4 258 258
390 112 886 RCS LYON - APE 2030 Z - E-mail: info.uk@blanchon.com
Internet : www.blanchon.com