














PRODUCT DATA CLICK ICONA PLANK RIGID CORE

PRODUCT			
Click LVT Rigid core SPC+ IXPE	EN ISO 10582		IBRIDO ICONA
Locking System			Click 14F
Classification	EN ISO 10874		23/33
SPECIFICATION			
Thickness	EN ISO 24337		6.5mm
Weight	EN ISO 24342		9.99kg/m ²
Wear Layer	EN ISO 24346		0.5mm
PRODUCT PROPERTIES			
PROPERTY	TEST METHOD		RESULT
Impact sound reduction	EN ISO 717-2:2013		20ΔLw (dB) (IXPE underlayment)
Indoor air certifications			Floorscore, A+, GreenGuard
Dimensionable stability	EN ISO 23999 (80 °C/6 h)		<0.167%
Abrasion resistance	BS ENO 13329-2016+A1-2017		AC4
Staining	EN 438-2		Pass (Grade 5)
Wear and scratch resistance	EN 438-2		Rating 4
Heat warpage	ISO 10582:2010(E)		≤2
Underfloor heating			OK (max+27°C)
Recycling			Suitable
Fire resistance	EN 13501-1		Bfl-s1
Residual indentation	EN ISO 24343-1		0.1mm
Chemical resistance	EN423		Class 0
Slip resistance	EN 13893 / DIN 51130		DS R11
Phthalate free			Yes
Click ICONA Plank	182 x 1220 x 6.5mm / 1.776m ² per box / 55 box per pallet		

Warranty
Residential
Lifetime
Light commercial
25 Year

CE
EN 14041

