

SAFETY DATA SHEET

HT700 FLOOR LACQUER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

▼Trade name

HT700 FLOOR LACQUER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Lacquering of wooden floors.

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Junckers Industrier A/S

Vaerftsvej 4

4600 Koege

Denmark

Tel. +45 70 80 30 00

E-mail

productsafety@junckers.dk

Revision

10/07/2023

SDS Version

1.0

23/03/2023 (1.0)

Date of previous version

1.4. Emergency telephone number The National Poisons Information Centre (NPIC)

Public: +353 (0) 1 809 2166 (7 days a week, 8am-10pm)

Healthcare professionals: +353 (0) 1 809 2566 (24 h service)

See also section 4 "First aid measures"

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP).

2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP).

2.2. Label elements

Hazard pictogram(s)

Not applicable.

Signal word

Not applicable.

Hazard statement(s)

Not applicable.

Precautionary statement(s)

General

Prevention

Response

Storage



Disposal

Hazardous substances

None known.

Additional labelling

EUH208, Contains 1,2-Benzisothiazol-3(2H)-one (BIT), 5-Chloro-2-methyl-2H-isothiazol-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1)). May produce an allergic reaction. EUH210, Safety data sheet available on request.

VOC

VOC content: ≤ 70 g/L

MAXIMUM VOC CONTENT (Phase II, category A/i (WB): 140 g/L) VOC content for product mixed with hardener: ≤ 100 g/L MAXIMUM VOC CONTENT (Phase II, category A/i (WB): 140 g/L)

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
2-(2-Butoxyethoxy)ethanol	CAS No.: 112-34-5 EC No.: 203-961-6 REACH: 01-2119475104-44 Index No.: 603-096-00-8	3-5%	Eye Irrit. 2, H319	[1], [3]
2-Dimethylaminoethanol	CAS No.: 108-01-0 EC No.: 203-542-8 REACH: 01-2119492298-24 Index No.: 603-047-00-0	<1%	Flam. Liq. 3, H226 Acute Tox. 4, H302 (ATE: 1187.00 mg/kg) Acute Tox. 4, H312 (ATE: 1219.00 mg/kg) Skin Corr. 1B, H314 Eye Dam. 1, H318 Acute Tox. 3, H331 (ATE: 6.00 mg/L) STOT SE 3, H335 (SCL: 5.00 %)	
1,2-Benzisothiazol-3(2H)-one (BIT)	CAS No.: 2634-33-5 EC No.: 220-120-9 REACH: 01-2120761540-60 Index No.: 613-088-00-6	<0,03%	Acute Tox. 4, H302 (ATE: 490.00 mg/kg) Skin Irrit. 2, H315 Skin Sens. 1, H317 (SCL: 0.05 %) Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	
5-Chloro-2-methyl-2H- isothiazol-3-one/2-Methyl-2H- isothiazol-3-one (3:1) (CMIT/MIT (3:1))	CAS No.: 55965-84-9 EC No.: 911-418-6 REACH: 01-2120764691-48 Index No.: 613-167-00-5	<0,0015%	EUH071 Acute Tox. 3, H301 (ATE: 64.00 mg/kg) Acute Tox. 2, H310 (ATE: 87.00 mg/kg) Skin Corr. 1C, H314 (SCL: 0.60 %) Skin Irrit. 2, H315 (SCL: 0.06 %) Skin Sens. 1A, H317 (SCL: 0.0015 %) Eye Dam. 1, H318 (SCL: 0.60 %) Eye Irrit. 2, H319 (SCL: 0.06 %) Acute Tox. 2, H330 (ATE: 0.17 mg/L) Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)	

HT700 FLOOR LACQUER Page 2 of 12



See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

- [1] European occupational exposure limit.
- [3] According to REACH, Annex XVII, the substance is subject to restrictions.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

▼ Eve contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

None known.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

. Carbon oxides (CO / CO2)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the National Poisons Information Centre (NPIC) on +353 (0) 1 809 256 (24 h service) in order to obtain further advice. Fire fighters should wear appropriate personal protective equipment.

SECTION 6: Accidental release measures



6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, soil, vermiculite or similar to collect liquid material. Subsequently, place in a suitable waste container.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

> 5 °C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-(2-Butoxyethoxy)ethanol

Long term exposure limit (8 hours) (mg/m³): 67.5

Long term exposure limit (8 hours) (ppm): 10

Short term exposure limit (15 minutes) (mg/m³): 101.2

Short term exposure limit (15 minutes) (ppm): 15

Annotations:

IOELV = Indicative Occupational Exposure Limit Values are health based limits set under the Chemical Agents Directive (98/24/EC).

2021 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019).

DNEL

1,2-Benzisothiazol-3(2H)-one (BIT)

	g/kg bw/day
Long term – Systemic effects - General population Inhalation 1,2 mg/	g/kg bw/day
	m³
Long term – Systemic effects - Workers Inhalation 6,81 mg	/m³

2-(2-Butoxyethoxy)ethanol

` , ,		
Duration:	Route of exposure:	DNEL:
Long term – Local effects - Workers	Inhalation	67,5 mg/m³
Short term – Local effects - Workers	Inhalation	101,2 mg/m³
Long term – Systemic effects - General population	Oral	6,25 mg/kg bw/day

2-Dimethylaminoethanol



Duration:	Route of exposure:	DNEL:
Long term – Local effects - Workers	Dermal	100 μg/cm²
Long term – Systemic effects - Workers	Dermal	0,25 mg/kg bw/day
Short term – Systemic effects - Workers	Dermal	1,2 mg/kg bw/day
Long term – Local effects - Workers	Inhalation	1,76 mg/m³
Long term – Systemic effects - General population	Inhalation	0,438 mg/m ³
Long term – Systemic effects - Workers	Inhalation	1,76 mg/m³
Short term – Local effects - Workers	Inhalation	13,53 mg/m³
Short term – Systemic effects - Workers	Inhalation	5,28 mg/m ³
Long term – Systemic effects - General population	Oral	0,148 mg/kg bw/day
5-Chloro-2-methyl-2H-isothiazol-3-one/2-Methyl-2H-is	othiazol-3-one (3:1) (CMIT/MIT (3:1))	
Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	0,02 mg/m ³
Long term – Local effects - Workers	Inhalation	0,02 mg/m³
Short term – Local effects - General population	Inhalation	0,04 mg/m³
Short term – Local effects - Workers	Inhalation	0,04 mg/m³
Long term – Systemic effects - General population	Oral	0,09 mg/kg bw/day
Short term – Systemic effects - General population	Oral	0,11 mg/kg bw/day
1,2-Benzisothiazol-3(2H)-one (BIT) Route of exposure:	Duration of Exposure:	PNEC:
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		4,03 µg/l
Freshwater sediment		49,9 μg/kg dw
Intermittent release (freshwater)		1,1 µg/l
Intermittent release (marine water)		0,11 μg/l
Marine water		0,403 μg/l
Marine water sediment		4,99 μg/kg dw
Sewage treatment plant		1,03 mg/l
Soil		3 mg/kg dw
2-(2-Butoxyethoxy)ethanol		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		1,1 mg/l
Freshwater sediment		4,4 mg/kg dw
Intermittent release (freshwater)		11 mg/l
Marine water		0,11 mg/l
Marine water sediment		0,44 mg/kg dw
Predators		56 mg/kg
Soil		0,32 mg/kg dw
2-Dimethylaminoethanol		
Route of exposure:	Duration of Exposure:	PNEC:
		0,066 mg/l
Freshwater		
Freshwater Freshwater sediment		0,246 mg/kg dw
		0,246 mg/kg dw 0,661 mg/l

HT700 FLOOR LACQUER Page 5 of 12



Marine water sediment		0,015 mg/kg dw
Sewage treatment plant		10 mg/l
Soil		0,01 mg/kg dw
5-Chloro-2-methyl-2H-isothiazol-3-one/2-Methyl-2H-isot	hiazol-3-one (3:1) (CMIT/MIT (3:1))	
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		3,39 µg/l
Freshwater sediment		0,027 mg/kg dw
Intermittent release (freshwater)		3,39 μg/l
Intermittent release (marine water)		3,39 μg/l
Marine water		3,39 μg/l
Marine water sediment		0,027 mg/kg dw
Sewage treatment plant		0,23 mg/l
Soil		0,01 mg/kg dw

8.2. ▼ Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

▼Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

Work situation	Туре	Class	Colour	Standards	
	Gas filter A	2 (medium capacity)	Brown	EN14387	
In case of spray application	Self contained breathing apparatus			EN137, EN139	

Ski

Work situation	Recommended	Type/Category	Standards	
	Dedicated work clothing should be worn	-	-	R
In case of spray application	Protective suit with hood	-	-	R

HT700 FLOOR LACQUER Page 6 of 12



Ha	nd protection				
	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
	Nitrile	0,4	> 480	EN374-2, EN374-3, EN388	

Eye protection

Type Standards

Safety glasses with side EN166 shields



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Whitish

Odour / Odour threshold

Faint

рΗ

8-9

Density (g/cm³)

1,04-1,05

Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

Testing not relevant or not possible due to the nature of the product.

Vapour pressure

Testing not relevant or not possible due to the nature of the product.

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C)

Testing not relevant or not possible due to the nature of the product.

Flammability (°C)

Testing not relevant or not possible due to the nature of the product.

Auto-ignition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water

Soluble

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.



Solubility in fat (q/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

VOC (g/L)

≤ 70

Mixed with hardener:

< 100

Other physical and chemical parameters

No data available.

Oxidizing properties

Testing not relevant or not possible due to the nature of the product.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance 2-Dimethylaminoethanol

Test method: OECD 401
Species: Rat
Route of exposure: Oral
Test: LD50
Result: 1187 mg/kg

Product/substance 2-Dimethylaminoethanol

Test method: OECD 402
Species: Rabbit
Route of exposure: Dermal
Test: LD50
Result: 1219 mg/kg

Product/substance 2-Dimethylaminoethanol

Test method:

Species:

Rat

Route of exposure:

Test:

Result:

OECD 403

Rat

Inhalation

LC50

Result:

6 mg/l

Product/substance 1,2-Benzisothiazol-3(2H)-one (BIT)

Test method: OECD 401

Species: Rat, Wistar, male/female

Route of exposure: Oral
Test: LD50
Result: 490 mg/kg

Product/substance 5-Chloro-2-methyl-2H-isothiazol-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1))

Species: Rat, Charles River CD, male

Route of exposure: Oral



Test: LD50 Result: 64 mg/kg

Product/substance 5-Chloro-2-methyl-2H-isothiazol-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1))

Species: Rabbit, Albino, male

Route of exposure: Dermal LD50 Result: 87 mg/kg

Product/substance 5-Chloro-2-methyl-2H-isothiazol-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1))

Test method: OECD 403

Species: Rat, Sprague-Dawley, male/female

Route of exposure: Inhalation
Test: LC50
Result: 0,17 mg/l

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized persons.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

None known.

Endocrine disrupting properties

Not applicable.

Other information

None known.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance 1,2-Benzisothiazol-3(2H)-one (BIT)

Test method: OECD 201

Species: Selenastrum capricornutum

Duration:72 hoursTest:ErC50Result:0,11 mg/l

Product/substance 1,2-Benzisothiazol-3(2H)-one (BIT)
Species: Selenastrum capricornutum

Duration: 72 hours
Test: NOErC
Result: 0,0403 mg/l

12.2. Persistence and degradability

Product/substance 2-(2-Butoxyethoxy)ethanol

Biodegradable: Yes

HT700 FLOOR LACQUER Page 9 of 12



Test method: OECD 301 C Result: 95 %

Product/substance 2-Dimethylaminoethanol

Biodegradable: Yes

Test method: OECD 301 C Result: > 60 %

Product/substance 5-Chloro-2-methyl-2H-isothiazol-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1))

Biodegradable: Yes
Test method: OECD 301 B
Result: 62 %

12.3. Bioaccumulative potential

Product/substance 2-(2-Butoxyethoxy)ethanol

Test method:

Potential bioaccumulation: No LogPow: 1

BCF: No data available.

Other information:

Product/substance 2-Dimethylaminoethanol

Test method:

Potential bioaccumulation: No LogPow: -0,55 BCF: 3,162

Other information:

Product/substance 1,2-Benzisothiazol-3(2H)-one (BIT)

Test method:

Potential bioaccumulation: No LogPow: 0,7 BCF: 6,62

Other information:

Product/substance 5-Chloro-2-methyl-2H-isothiazol-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1))

Test method:

Potential bioaccumulation: No LogPow: 0,75

BCF: No data available.

Other information:

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

Not applicable.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

08 01 12 Waste paint and varnish other than those mentioned in 08 01 11

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

HT700 FLOOR LACQUER Page 10 of 12



SECTION 14: Transport information

	14.1 14.2 UN / ID UN proper shipping name	14.3 Hazard class(es)	14.4 14.5 Other PG* Env** information:
ADR		-	
IMDG		-	
IATA		-	

^{*} Packing group

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

Not applicable.

Additional information

Not applicable.

Sources

Maternity Protection Act 1994 (34/1994) with later amendments.

S.I. No. 199/2007 - Limitation of Emissions of Volatile Organic Compounds Due to the Use of Organic Solvents in Certain Paints, Varnishes and Vehicle Refinishing Products Regulations 2007.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

EUH071, Corrosive to the respiratory tract.

H226, Flammable liquid and vapour.

H301, Toxic if swallowed.

H302, Harmful if swallowed.

H310, Fatal in contact with skin.

H312, Harmful in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H330, Fatal if inhaled.

H331, Toxic if inhaled.

H335, May cause respiratory irritation.

H400, Very toxic to aquatic life.

^{**} Environmental hazards





H410, Very toxic to aquatic life with long lasting effects.

H411, Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH = CLP-specific hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of classification and labelling of chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = Logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = Specific Concentration Limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time Weighted Average

UN = United Nations

UVCB = Substances of Unknown or Variable composition, Complex reaction products or Biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and very Bioaccumulative

Additional information

Not applicable.

▼The safety data sheet is validated by

ULS

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: IE-en