

### SAFETY DATA SHEET

# MT500 FLOOR LACQUER

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name

MT500 FLOOR LACQUER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Lacquering of wooden floors.

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

## Company and address

# **Junckers Industrier A/S**

Vaerftsvej 4

4600 Koege

Denmark

Tel. +45 70 80 30 00

### E-mail

productsafety@junckers.dk

Revision

28/08/2023

**SDS Version** 

1.1

10/07/2023 (1.0)

Date of previous version

1.4. Emergency telephone number
The National Poisons Information Centre (NPIC)

Public: +353 (0) 1 809 2166 (7 days a week, 8am- 10pm)

Healthcare professionals: +353 (0) 1 809 2566 (24 h service)

See also section 4 "First aid measures"

## SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP).

# 2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP).

### 2.2. Label elements

Hazard pictogram(s)

Not applicable.

Signal word

Not applicable.

Hazard statement(s)

Not applicable.

Precautionary statement(s)

General

Prevention

.

Response

. -

Storage



# Disposal

# Hazardous substances

None known.

## Additional labelling

EUH208, Contains 1,2-Benzisothiazol-3(2H)-one (BIT), 5-Chloro-2-methyl-2H-isothiazol-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1)), 2-Methyl-2H-isothiazol-3-one (MIT). May produce an allergic reaction. EUH210, Safety data sheet available on request.

### VOC

VOC content: ≤ 60 g/L

MAXIMUM VOC CONTENT (Phase II, category A/i (WB): 140 g/L)

### 2.3. Other hazards

## Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

# SECTION 3: Composition/information on ingredients

## 3.1. Substances

Not applicable. This product is a mixture.

## 3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
(2- Methoxymethylethoxy)propan ol	CAS No.: 34590-94-8 EC No.: 252-104-2 REACH: 01-2119450011-60 Index No.:	3-5%		[1]
Propane-1,2-diol, propoxylated	CAS No.: 25322-69-4 EC No.: REACH: Index No.:	<1,5%	Acute Tox. 4, H302	
Triethylamine	CAS No.: 121-44-8 EC No.: 204-469-4 REACH: 01-2119475467-26 Index No.: 612-004-00-5	<1%	Flam. Liq. 2, H225 Acute Tox. 4, H302 (ATE: 730.00 mg/kg) Acute Tox. 3, H311 (ATE: 580.00 mg/kg) Skin Corr. 1A, H314 Eye Dam. 1, H318 Acute Tox. 3, H331 (ATE: 7.22 mg/L) STOT SE 3, H335 (SCL: 1.00 %)	[1]
1,2-Benzisothiazol-3(2H)-one (BIT)	CAS No.: 2634-33-5 EC No.: 220-120-9 REACH: 01-2120761540-60 Index No.: 613-088-00-6	<0,03%	Acute Tox. 4, H302 (ATE: 490.00 mg/kg) Skin Irrit. 2, H315 Skin Sens. 1, H317 (SCL: 0.05 %) Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	
5-Chloro-2-methyl-2H- isothiazol-3-one/2-Methyl-2H- isothiazol-3-one (3:1) (CMIT/MIT (3:1))	CAS No.: 55965-84-9 EC No.: 911-418-6 REACH: 01-2120764691-48 Index No.: 613-167-00-5	<0,0015%	EUH071 Acute Tox. 3, H301 (ATE: 64.00 mg/kg) Acute Tox. 2, H310 (ATE: 87.00 mg/kg) Skin Corr. 1C, H314 (SCL: 0.60 %) Skin Irrit. 2, H315 (SCL: 0.06 %) Skin Sens. 1A, H317 (SCL: 0.0015 %) Eye Dam. 1, H318 (SCL: 0.60 %) Eye Irrit. 2, H319 (SCL: 0.06 %) Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)	
2-Methyl-2H-isothiazol-3-one	CAS No.: 2682-20-4	<0,0015%	EUH071	

MT500 FLOOR LACQUER Page 2 of 14



(MIT) EC No.: 220-239-6

REACH: 01-2120764690-50

Index No.:

Acute Tox. 3, H301 (ATE: 120.00 mg/kg) Acute Tox. 3, H311 (ATE: 242.00 mg/kg)

Skin Corr. 1B, H314

Skin Sens. 1A, H317 (SCL: 0.0015 %)

Eye Dam. 1, H318 Acute Tox. 2, H330

Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

### Other information

[1] European occupational exposure limit.

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

# Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

## Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

### Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

### **Burns**

Not applicable.

## 4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

# 4.3. ▼Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## Information to medics

Bring this safety data sheet or the label from this product.

## **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

# 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

MT500 FLOOR LACQUER Page 3 of 14

### Carbon oxides (CO / CO2)

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the National Poisons Information Centre (NPIC) on +353 (0) 1 809 256 (24 h service) in order to obtain further advice. Fire fighters should wear appropriate personal protective equipment.

### SECTION 6: Accidental release measures

# 6.1. ▼ Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

## 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

## 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, soil, vermiculite or similar to collect liquid material. Subsequently, place in a suitable waste container.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

# 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

## Recommended storage material

Always store in containers of the same material as the original container.

## Storage temperature

> 5 °C

# Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

# 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

# SECTION 8: Exposure controls/personal protection

# 8.1. Control parameters

(2-Methoxymethylethoxy)propanol

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 308

Long term exposure limit (8 hours) (ppm): 50

Annotations:

IOELV = Indicative Occupational Exposure Limit Values are health based limits set under the Chemical Agents Directive (98/24/EC).

Sk = Substance, which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body.

# Triethylamine

Long term exposure limit (8 hours) (mg/m³): 8.4

Long term exposure limit (8 hours) (ppm): 2

Short term exposure limit (15 minutes) (mg/m³): 12.6

Short term exposure limit (15 minutes) (ppm): 3

Annotations:

IOELV = Indicative Occupational Exposure Limit Values are health based limits set under the Chemical Agents Directive (98/24/EC).

Sk = Substance, which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body.



2021 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019).

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	121 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	283 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	37,2 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	308 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	36 mg/kg bw/day
1,2-Benzisothiazol-3(2H)-one (BIT)		
Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	0,345 mg/kg bw/c
Long term – Systemic effects - Workers	Dermal	0,966 mg/kg bw/c
Long term – Systemic effects - General population	Inhalation	1,2 mg/m³
Long term – Systemic effects - Workers	Inhalation	6,81 mg/m³
2-Methyl-2H-isothiazol-3-one (MIT)		
Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	0,021 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	0,021 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	0,043 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	0,043 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	0,027 mg/kg bw/d
Short term – Systemic effects - General population	Oral	0,053 mg/kg bw/d
5-Chloro-2-methyl-2H-isothiazol-3-one/2-Methyl-2H-isoth	iazol-3-one (3:1) (CMIT/MIT (3:1))	
Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	0,02 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	0,02 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	0,04 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	0,04 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	0,09 mg/kg bw/da
Short term – Systemic effects - General population	Oral	0,11 mg/kg bw/da
Triethylamine		
Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	12,1 mg/kg bw/da
Long term – Local effects - Workers	Inhalation	8,4 mg/m³
Short term – Local effects - Workers	Inhalation	12,6 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	8,4 mg/m³
Short term – Systemic effects - Workers	Inhalation	12,6 mg/m³
EC (2-Methoxymethylethoxy)propanol		
Route of exposure:	Duration of Exposure:	PNEC:
	· P · · · · ·	•
Freshwater		19 mg/l

MT500 FLOOR LACQUER Page 5 of 14



Intermittent release (freshwater)		190 mg/l
Marine water		1,9 mg/l
Marine water sediment		7,02 mg/kg dw
Sewage treatment plant		4168 mg/l
Soil		2,74 mg/kg dw
10.0		, 5 5
1,2-Benzisothiazol-3(2H)-one (BIT)	Duration of Functions	DNIEC.
Route of exposure: Freshwater	Duration of Exposure:	PNEC:
Freshwater Freshwater sediment		4,03 µg/l
		49,9 μg/kg dw
Intermittent release (freshwater)		1,1 µg/l
Intermittent release (marine water)		0,11 μg/l
Marine water		0,403 μg/l
Marine water sediment		4,99 μg/kg dw
Sewage treatment plant		1,03 mg/l
Soil		3 mg/kg dw
2-Methyl-2H-isothiazol-3-one (MIT)		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		3,39 µg/l
Intermittent release (freshwater)		3,39 μg/l
Intermittent release (marine water)		3,39 μg/l
Marine water		3,39 µg/l
Sewage treatment plant		0,23 mg/l
Soil		0,047 mg/kg dw
5-Chloro-2-methyl-2H-isothiazol-3-one/2-Methyl-2H-is	othiazol-3-one (3:1) (CMIT/MIT (3:1))	
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		3,39 μg/l
Freshwater sediment		0,027 mg/kg dw
Intermittent release (freshwater)		3,39 µg/l
Intermittent release (marine water)		3,39 μg/l
Marine water		3,39 µg/l
Marine water sediment		0,027 mg/kg dw
Sewage treatment plant		0,23 mg/l
Soil		0,01 mg/kg dw
SUII		
Triethylamine  Route of exposure:	Duration of Exposure:	PNEC:
Friethylamine	Duration of Exposure:	<b>PNEC:</b> 0,11 mg/l
Triethylamine  Route of exposure:  Freshwater	Duration of Exposure:	
Triethylamine Route of exposure:	Duration of Exposure:	0,11 mg/l
Triethylamine  Route of exposure:  Freshwater  Freshwater sediment	Duration of Exposure:	0,11 mg/l 1,575 mg/kg dw
Friethylamine  Route of exposure:  Freshwater  Freshwater sediment  Intermittent release (freshwater)	Duration of Exposure:	0,11 mg/l 1,575 mg/kg dw 0,08 mg/l
Triethylamine  Route of exposure:  Freshwater  Freshwater sediment  Intermittent release (freshwater)  Marine water	Duration of Exposure:	0,11 mg/l 1,575 mg/kg dw 0,08 mg/l 0,011 mg/l

# 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis. General recommendations

MT500 FLOOR LACQUER Page 6 of 14



Smoking, drinking and consumption of food is not allowed in the work area.

# **Exposure scenarios**

There are no exposure scenarios implemented for this product.

## **Exposure limits**

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

# Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

# Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

# Measures to avoid environmental exposure

No specific requirements.

## Individual protection measures, such as personal protective equipment

### Generally

Use only CE marked protective equipment.

# **Respiratory Equipment**

<b>Work situation</b>	Туре	Class	Colour	Standards	
In case of insufficient ventilation	Gas filter A	2 (medium capacity)	Brown	EN14387	
In case of spray application	Combination filter AP	2	Brown/white	EN14387	
in protection					
Work situation	Recommended	Type/Ca	ategory Sta	andards	
	Dedicated work clo	thing -	-		R

	should be worn		R
In case of spray application	Protective suit with hood	-	

# Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0,4	> 480	EN374-2, EN374-3, EN388	



Work situation	Туре	Standards	
In case of spray application	Safety glasses with side shields	EN166	

# SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

MT500 FLOOR LACQUER Page 7 of 14



```
Whitish
  Odour / Odour threshold
      Faint
  рН
      8-9
  Density (q/cm<sup>3</sup>)
      1,05-1,07
  Kinematic viscosity
      Testing not relevant or not possible due to the nature of the product.
  Particle characteristics
      Does not apply to liquids.
Phase changes
  Melting point/Freezing point (°C)
      Testing not relevant or not possible due to the nature of the product.
  Softening point/range (waxes and pastes) (°C)
      Does not apply to liquids.
  Boiling point (°C)
      Testing not relevant or not possible due to the nature of the product.
  Vapour pressure
      Testing not relevant or not possible due to the nature of the product.
  Relative vapour density
      Testing not relevant or not possible due to the nature of the product.
  Decomposition temperature (°C)
      Testing not relevant or not possible due to the nature of the product.
Data on fire and explosion hazards
  Flash point (°C)
      Testing not relevant or not possible due to the nature of the product.
  Flammability (°C)
      Testing not relevant or not possible due to the nature of the product.
  Auto-ignition temperature (°C)
      Testing not relevant or not possible due to the nature of the product.
  Lower and upper explosion limit (% v/v)
      Testing not relevant or not possible due to the nature of the product.
Solubility
  Solubility in water
      Soluble
  n-octanol/water coefficient
      Testing not relevant or not possible due to the nature of the product.
  Solubility in fat (q/L)
      Testing not relevant or not possible due to the nature of the product.
9.2. Other information
  VOC (q/L)
      ≤ 60
  Other physical and chemical parameters
      No data available.
  Oxidizing properties
      Testing not relevant or not possible due to the nature of the product.
```

# SECTION 10: Stability and reactivity

# 10.1. Reactivity

No data available.

## 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

## 10.3. Possibility of hazardous reactions

None known.

# 10.4. Conditions to avoid

None known.

## 10.5. Incompatible materials



Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

## 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance Triethylamine
Test method: OECD 401
Species: Rat, male/female

Route of exposure: Oral
Test: LD50
Result: 730 mg/kg

Product/substance Triethylamine Test method: OECD 403

Species: Rat, Sprague-Dawley, male/female

Route of exposure: Inhalation
Test: LC50
Result: 7,22 mg/l

Product/substance Triethylamine Test method: OECD 402

Species: Rabbit, New Zealand Black, male

Route of exposure: Dermal
Test: LD50
Result: 580 mg/kg

Product/substance 1,2-Benzisothiazol-3(2H)-one (BIT)

Test method: OECD 401

Species: Rat, Wistar, male/female

Route of exposure: Oral
Test: LD50
Result: 490 mg/kg

Product/substance 5-Chloro-2-methyl-2H-isothiazol-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1))

Species: Rat, Charles River CD, male

Route of exposure: Oral Test: LD50 Result: 64 mg/kg

Product/substance 5-Chloro-2-methyl-2H-isothiazol-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1))

Species: Rabbit, Albino, male

Route of exposure: Dermal Test: LD50 Result: 87 mg/kg

Product/substance 5-Chloro-2-methyl-2H-isothiazol-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1))

Test method: OECD 403
Species: Rat, Sprague-Dawley, male/female

Route of exposure:

Test:

LC50

Result:

0,17 mg/l

Product/substance 2-Methyl-2H-isothiazol-3-one (MIT)

Species: Rat, male/female

Route of exposure: Oral
Test: LD50
Result: 120 mg/kg

Product/substance 2-Methyl-2H-isothiazol-3-one (MIT)

Test method: OECD 402 Species: Rat, male/female

MT500 FLOOR LACQUER Page 9 of 14



Route of exposure: Dermal
Test: LD50
Result: 242 mg/kg

Product/substance 2-Methyl-2H-isothiazol-3-one (MIT)

Test method: OECD 403

Species: Rabbit, male/female

Route of exposure: Inhalation Test: LC50 Result: 0,11 mg/l

## Skin corrosion/irritation

Based on available data, the classification criteria are not met.

### Serious eve damage/irritation

Based on available data, the classification criteria are not met.

### Respiratory sensitisation

Based on available data, the classification criteria are not met.

#### Skin sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized persons.

### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

### Carcinogenicity

Based on available data, the classification criteria are not met.

### Reproductive toxicity

Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

# Long term effects

None known.

# Endocrine disrupting properties

Not applicable.

# Other information

None known.

# SECTION 12: Ecological information

12.1. Toxicity

Product/substance 1,2-Benzisothiazol-3(2H)-one (BIT)

Test method: OECD 201

Species: Selenastrum capricornutum

Duration: 72 hours
Test: ErC50
Result: 0,11 mg/l

Product/substance 1,2-Benzisothiazol-3(2H)-one (BIT) Species: Selenastrum capricornutum

Duration:72 hoursTest:NOErCResult:0,0403 mg/l

Product/substance 2-Methyl-2H-isothiazol-3-one (MIT)

Species: Skeletonema costatum

Duration: 72 hours
Test: EC50
Result: 0,072 mg/l

Product/substance 2-Methyl-2H-isothiazol-3-one (MIT)

MT500 FLOOR LACQUER Page 10 of 14



Species: Selenastrum capricornutum

Duration: 72 hours
Test: NOEC
Result: 0,05 mg/l·

12.2. Persistence and degradability

Product/substance (2-Methoxymethylethoxy)propanol

Biodegradable: Yes
Test method: OECD 301 F
Result: 79 %

Product/substance Triethylamine

Biodegradable: Yes

Test method: OECD 301 B Result: 80 %

Product/substance 5-Chloro-2-methyl-2H-isothiazol-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1))

Biodegradable: Yes

Test method: OECD 301 B Result: 62 %

Product/substance 2-Methyl-2H-isothiazol-3-one (MIT)

Biodegradable: No
Test method: OECD 301 B
Result: 50 %

12.3. Bioaccumulative potential

Product/substance (2-Methoxymethylethoxy)propanol

Test method:

Potential bioaccumulation: No LogPow: 0,004

BCF: No data available.

Other information:

Product/substance Triethylamine

Test method:

Potential bioaccumulation: No LogPow: 1,45 BCF: 0,5

Other information:

Product/substance 1,2-Benzisothiazol-3(2H)-one (BIT)

Test method:

Potential bioaccumulation: No LogPow: 0,7 BCF: 6,62

Other information:

Product/substance 5-Chloro-2-methyl-2H-isothiazol-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1))

Test method:
Potential bioaccumulation: N

Potential bioaccumulation: No LogPow: 0,75

BCF: No data available.

Other information:

Product/substance 2-Methyl-2H-isothiazol-3-one (MIT)

Test method:

Potential bioaccumulation: No LogPow: -0,49

BCF: No data available.

Other information:

## 12.4. Mobility in soil

No data available.

# 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or



vPvB.

12.6. Endocrine disrupting properties

Not applicable.

12.7. Other adverse effects

None known.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

08 01 12 Waste paint and varnish other than those mentioned in 08 01 11

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

## **SECTION 14: Transport information**

	14.1 UN /	14.2 ID UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

<sup>\*</sup> Packing group

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

No special.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

Not applicable.

Additional information

Not applicable.

Sources

Maternity Protection Act 1994 (34/1994) with later amendments.

S.I. No. 199/2007 - Limitation of Emissions of Volatile Organic Compounds Due to the Use of Organic Solvents in Certain Paints, Varnishes and Vehicle Refinishing Products Regulations 2007.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on

classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

## 15.2. Chemical safety assessment

No

# SECTION 16: Other information

<sup>\*\*</sup> Environmental hazards



### ▼ Full text of H-phrases as mentioned in section 3

EUH071, Corrosive to the respiratory tract.

H225, Highly flammable liquid and vapour.

H301, Toxic if swallowed.

H302, Harmful if swallowed.

H310, Fatal in contact with skin.

H311, Toxic in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H330, Fatal if inhaled.

H331, Toxic if inhaled.

H335, May cause respiratory irritation.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

H411, Toxic to aquatic life with long lasting effects.

## Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH = CLP-specific hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of classification and labelling of chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = Logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = Specific Concentration Limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time Weighted Average

**UN = United Nations** 

UVCB = Substances of Unknown or Variable composition, Complex reaction products or Biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and very Bioaccumulative

# Additional information

Not applicable.

# ▼ The safety data sheet is validated by

ULS

# Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue





triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: IE-en