

## Safety Data Sheet

### MAPEPROOF ESM parte A

Safety Data Sheet dated 23/4/2010, version 6

#### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Trade name: MAPEPROOF ESM parte A

Product type and use: Epoxy resins.

Supplier:

MAPEI S.p.A. -Via Cafiero 22 - Milan -ITALY

Emergency telephone number of the company and/or of an authorised advisory centre:

MAPEI S.p.A. - Tel. +(39)02376731


Poison Centre - Ospedale di Niguarda - Milan - Tel. +39/02/66101029

Competent person responsible for the safety data sheet:

sicurezza@mapei.it

#### 2. HAZARDS IDENTIFICATION

Properties / Symbols:

 Xi Irritant

 N Dangerous for the environment

R Phrases:

R36/38 Irritating to eyes and skin.

R43 May cause sensitization by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

If brought into contact with the eyes, the product causes irritation that may last for over 24 hours, and if brought into contact with the skin it causes significant inflammation with erythema, scabs, and oedema.

If brought into contact with the skin, the product may cause sensitisation of the skin.

This preparation contains low molecular weight epoxy resins. Cross sensitisation to other epoxies is possible. Avoid also exposure to spray mist and vapour.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components within the meaning of EEC directive 67/548 and corresponding classification:

50% - 60% Reaction product: bisphenol-A-(epichlorhydrin)

Epoxy resin (number average molecular weight = 700)

N. EEC/67/548: 603-074-00-8 CAS: 25068-38-6 EC: 500-033-5

Xi,N; R36/38-43-51-53

20% - 25% oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

N. EEC/67/548: 603-103-00-4 CAS: 68609-97-2 EC: 271-846-8

Xi; R38-43

10% - 12.5% Epoxy resin. Reaction product: bisphenol-F-epichlorhydrin (number average molecular weight <= 700)

CAS: 9003-36-5 EC: 500-006-8

Xi,N; R36/38-43-51-53

## Safety Data Sheet

### MAPEPROOF ESM parte A

---

#### 4. FIRST AID MEASURES

Contact with skin:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Contact with eyes:

Wash immediately and thoroughly with running water, keeping eyelids raised, for at least 10 minutes. Following this, protect the eyes with sterile gauze or a clean, dry, handkerchief.

OBTAIN A MEDICAL EXAMINATION.

Swallowing:

A suspension of activated charcoal in water, or petroleum jelly may be administered.

Inhalation:

Ventilate the premises. The patient is to be removed immediately from the premises contaminated and made to rest in a well ventilated area. Should the patient feel unwell, consult a physician.

---

#### 5. FIRE-FIGHTING MEASURES

Recommended extinguishers:

Water, CO<sub>2</sub>, Foam, Chemical powders, according to the materials involved in the fire.

Extinguishers not to be used:

None in particular.

Risks arising from combustion:

The original ingredients or unidentified toxic and/or irritant compounds may be present in the combustion fumes.

In case of incomplete combustion or pyrolysis, phenolic oxide and/or carbonic oxide can be formed.

Avoid inhaling the fumes.

Protective equipment:

Use protection for the airways.

---

#### 6. ACCIDENTAL RELEASE MEASURES

Measures for personal safety:

Use a mask, gloves and protective clothing.

Environmental measures:

Limit leakages with earth or sand.

None in particular.

If the product has escaped into a water course, into the drainage system, or has contaminated the ground or vegetation, notify the competent authorities.

Cleaning methods:

Rapidly recover the product, wearing protective clothing.

If the product is in a liquid form, stop it from entering the drainage system.

Recover the product for re-use if possible, or for disposal. The product might, where appropriate, be absorbed by inert material.

After the product has been recovered, rinse the area and materials involved with water.

---

#### 7. HANDLING AND STORAGE

Handling precautions:

Avoid contact and inhalation of the vapours. See, too, paragraph 8 below.

Do not eat or drink while working.

Incompatible materials:

None in particular.

Storage conditions:

Always keep the containers tightly closed.

Instructions as regards storage premises:

Adequately ventilated premises.

---

## Safety Data Sheet

### MAPEPROOF ESM parte A

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Precautionary measures:

Give adequate ventilation to the premises where the product is stored and/or handled.

Respiratory protection:

Not needed for normal use.

Protection for hands:

Use protective rubber gloves.

The use of LLPDE (0,06 mm), nitrile (0,4) or butyl (0,5 mm) gloves is suggested.

Latex gloves are not recommended.

Eye protection:

Not needed for normal use.

Protection for skin:

Use clothing that provides comprehensive protection to the skin.

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Exposure limit value of single components:

None

Carry out the control of the concentrations of the substances with exposure limits assigned, in the working place according to local dispositions

---

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	liquid
Colour:	transparent
Odour:	typical
pH:	N.A.
Melting point:	N.A.
Boiling point:	N.A.
Flash point:	== °C
Solid/gas flammability:	N.A.
Autoignition temperature:	== °C
Explosion limits(by volume):	==
Oxidizing properties:	N.A.
Vapour pressure:	N.A.
Relative density:	1.17 g/cm <sup>3</sup> (23°C)
Solubility in water:	insoluble
Lipid solubility:	soluble
Viscosity:	350 mPa.s (23°C)
Vapour density (air=1):	N.A.

---

#### 10. STABILITY AND REACTIVITY

Conditions to avoid:

Stable under normal conditions.

It may catch fire on contact with powerful oxidising agents.

---

#### 11. TOXICOLOGICAL INFORMATION

## Safety Data Sheet

### MAPEPROOF ESM parte A

#### Route(s) of entry:

Ingestion: Yes  
Inhalation: Yes  
Contact: Yes

#### Toxicological information related to the product:

No toxicological data are available at the moment on the product itself.

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Set out below is the toxicological information relating to the main substances in the preparation.

The product does not contain toxicologically relevant substances.

#### Corrosive/Irritating Properties:

##### Skin:

The product can cause irritation by contact.

##### Eye:

The product can cause irritation by contact

#### Sensitizing Properties:

Frequent contact may cause sensitization.

#### Cancerogenic Effects:

No effects are known.

#### Mutagenic Effects:

No effects are known.

#### Teratogenic Effects:

No effects are known.

#### Additional Information:

Liquid epoxy resin contained in this material causes only minor skin irritation. However, all epoxy resins are capable of causing sensitizing of the skin.

Susceptibility to skin irritation and sensitization varies from person to person.

In a sensitized individual the allergic dermatitis may not appear until after several days or weeks of frequent and prolonged contact.

Therefore, even though the skin irritation potential is slight, skin contact should be avoided. Once sensitization has occurred, exposure of the skin to very small quantities of the material may cause erythema and edema.

---

## 12. ECOLOGICAL INFORMATION

Biodegradability: no data available on the preparation.

Adopt good industrial practices, so that the product is not released into the environment.

List of environmentally dangerous substances contained in this preparation and their classification:

50% - 60% Reaction product: bisphenol-A-(epichlorhydrin)

Epoxy resin (number average molecular weight = 700)

N. EEC/67/548: 603-074-00-8 CAS: 25068-38-6 EC: 500-033-5

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

10% - 12.5% Epoxy resin. Reaction product: bisphenol-F-epichlorhydrin (number average molecular weight <= 700)

CAS: 9003-36-5 EC: 500-006-8

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

---

## 13. DISPOSAL CONSIDERATIONS

Recover if possible. In so doing, comply with the local and national regulations currently in force.

Dispose of this material and its container to hazardous or special waste collection point.

Avoid release to the environment. Refer to special instructions/Safety data sheets.

Where applicable, refer to the following regulatory provisions : 91/156/EEC, 91/689/EEC, 94/62/EC

## Safety Data Sheet

### MAPEPROOF ESM parte A

and subsequent amendments.

Disposal of hardened product (EC waste code) : 08 04 10

Disposal of not hardened product (EC waste code) : 08 04 09

The suggested European waste code is just based on the composition of the product.

According to the specific process or application field a different waste code may be necessary.

---

#### 14. TRANSPORT INFORMATION

UN Number:	3082
Rail/Road(RID/ADR):	9, III
LIMITED QUANTITY (3.4.6. ADR e 3.4.2. IMDG)	
Sea (IMO/IMDG):	9, III
Dangerous goods in limited quantities	
MAR/POL 73/78,Annex III:	No
Air (ICAO/IATA):	9, III

---

#### 15. REGULATORY INFORMATION

Council Directive 67/548/EEC (Classification, packaging and labelling of dangerous substances) and subsequent amendments. Commission Directive 1999/45/EC (Classification, packaging and labelling of dangerous preparation) and subsequent amendments. Commission Directive 98/24/EC (Protection of the health and safety of workers from the risk related to chemical agent). Commission Directive 2000/39/EC (Occupational exposure limit values). Regulation (EC) No 1907/2006 (REACH).

Symbols:

Xi Irritant

N Dangerous for the environment

R Phrases:

R36/38 Irritating to eyes and skin.

R43 May cause sensitization by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S Phrases:

S24 Avoid contact with skin.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37 Wear suitable gloves.

S56 Dispose of this material and its container to hazardous or special waste collection point.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Contents:

Reaction product: bisphenol-A-(epichlorhydrin)

Epoxy resin (number average molecular weight = 700)

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Epoxy resin. Reaction product: bisphenol-F-epichlorhydrin (number average molecular weight <= 700)

Special Provisions:

Contains epoxy constituents. See information supplied by the manufacturer.

---

#### 16. OTHER INFORMATION

Main bibliographic sources:

NIOSH - Registry of toxic effects of chemical substances

Istituto Superiore di Sanità - Inventario Nazionale Sostanze Chimiche

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,

Commission of the European Communities

ACGIH - Threshold Limit Values - 2004 edition

## Safety Data Sheet

### MAPEPROOF ESM parte A

SAX'S - Dangerous properties of industrial materials

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Text of R phrases referred to under heading 3:

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R43 May cause sensitization by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Paragraphs modified from the previous revision:

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
2. HAZARDS IDENTIFICATION
3. COMPOSITION/INFORMATION ON INGREDIENTS
6. ACCIDENTAL RELEASE MEASURES
7. HANDLING AND STORAGE
8. EXPOSURE CONTROLS/PERSONAL PROTECTION
9. PHYSICAL AND CHEMICAL PROPERTIES
11. TOXICOLOGICAL INFORMATION
12. ECOLOGICAL INFORMATION
13. DISPOSAL CONSIDERATIONS
15. REGULATORY INFORMATION