

## STICK 2 CONTACT ADHESIVE THINNER & CLEANER



Colour	Product Code	Pack Size	Box Qty
-	CONTHIN025	250ml	10
	CONTHIN1	1Ltr	10
	CONTHIN2	2.5Ltr	4

### Product Description

STICK 2 CONTACT ADHESIVE THINNER AND CLEANER is a solvent based thinner and cleaner for most common contact adhesives.

### Areas For Use

- Diluting contact adhesives for priming purposes
- Cleaning/removal of wet and dry contact adhesives
- Degreasing surfaces prior to application of contact adhesives.

### Limitations

**CAUTION; SOLVENT BASED PRODUCT; Strictly observe Health and Safety precautions given on this label and avoid contact with skin and eyes. Do not ingest. Avoid inhalation of vapours/fumes. Highly Flammable product - Avoid all sources of ignition. Do not smoke during use.**

Avoid contact with sensitive surfaces Always test a small inconspicuous area prior to full coverage. As the manufacturer cannot know all the uses its products may be put to, it is the users responsibility to determine suitability of use. If in doubt, contact Technical Services Department for advice.

***Important: This product is solvent based and should only be used according to the instructions. To prevent solvent abuse, this product should only be sold to adults for its intended use. For self-service retail display, please request empty tins to be used for display and store product separately***

### Application

**As a Thinner;** For priming purposes on heavily porous surfaces (eg MDF). Dilute 1 part contact adhesive to 6 parts thinners. Brush on surface and allow to dry. Apply contact adhesive as directed.

**As a cleaner;** Wear protective gloves and apply to a dirty rag. Rub off unwanted adhesive. Soak tools in this solution as required. Also suitable for degreasing surfaces prior to applying contact adhesive. CAUTION; This product is very aggressive and may damage surrounding surfaces. Always test a small inconspicuous area before use for compatibility.

### Health & Safety

Consult MSDS for full list of hazards.

### Storage

Store in cool dry conditions between 5 and 25°C away from direct sunlight and all sources of ignition.

### Shelf Life

36 months in original unopened containers when stored as detailed above.

*The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.*