

03/2023

DIMENSIONS		
Collection	CLASSIC PLANK	TILES
Width	189 mm	303 mm
Length	1251 mm	610 mm
Number of panels per pack	9 Panels	10 Panels
m <sup>2</sup> per pack	2,128 m <sup>2</sup>	1,848 m <sup>2</sup>
Weight per pack	±14,15 kg	± 12,33 kg
Total thickness	ISO 24346 5mm (= 4 + 1mm attached underlay)	5mm (= 4 + 1mm attached underlay)
Finishing	Superguard Prime	
Tongue and groove	Uniclic connection	

FACTORY WARRANTY		
Usage class	EN ISO 10874	Class 33
Product norm	EN 16511:2014 + A1:2019	
CE / UK CA	EN 14041:2004 / AC: 2006	DOP: see end label on pack
Warranty	Residential use Commercial use	See warranty conditions See warranty conditions
		25 years 0 years - on request up to 5 years

GENERAL DATA				
	METHOD	PARAMETERS	NORM REQUIREMENTS	ELKA VALUES
Wear resistance	EN 16511:2014 + A1:2019			OK
Impact resistance	EN 13329 - Annex F		≥ 1600 mm	OK
Castor chairs	EN 425	25000 cycles	No delamination, no disturbance	OK
Displacement of furniture feet	EN 424	Foot 0.1 mm / 32 kg		No visible damage
Residual indentation	EN ISO 24343-1		≤ 0.2 mm	OK
Resistance against staining	EN 438-2		Gr1(10min)&Gr2: grade5 + Gr3,grade4	OK
Dimensional stability	ISO 23999	6 hrs at 80°C Cupping	< 0,25% < 1 mm	OK OK
Fire classification	EN 13501-1			BIH-s1
UV resistance	ISO 105 B02	Blue reference	Class	OK
Slip resistance	EN 13893 DIN 51130:2014		> 6	DS R9
Thermal resistance	EN 12667	Underlay attached		0,033 m <sup>2</sup> K/W
Floor heating		Appropriate for all standard heating systems IN cement flooring. NOT appropriate for heating films and alternatives. Max contact temp ≤ 27°C. See separate installation instructions.		

ENVIRONMENT & CERTIFICATES			
AFFSET			A+
Formaldehyde emission	EN 14041:2004 / AC: 2006	No added formaldehyde in production	< detection limit
TVOC 28 days	ISO 16000 part 9-6	AgBB requirement after 28 days	<1000 µg/m <sup>3</sup>
Content	Heavy metals+ lead/cadmium		NOT present
DANGEROUS SUBSTANCES	Carcinogenic, mutagenic or reprotoxic substances class 1A and 1B (candidate list)		NOT present
Plasticizer	Ortho-phthalate free plasticizer		