

SAFETY DATA SHEET

Page 1 of 3

Fiddes Hard Wax Oil

Revision 7 Revision date 20-Jan-2011

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name Fiddes Hard Wax Oil
Company Fiddes & Son Ltd

Florence Works, Brindley Road, Cardiff, South Glamorgan, CF11 8TX

info@fiddes.co.uk www.fiddes.co.uk

Telephone +44 (0)29 2034 0323 Fax +44 (0)29 2034 3235

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

Conc. CAS EINECS Symbols/Risk phrases

Dearomatised White Spirit 20 - 30% 64742-48-9 265-150-3 Xn; R65 R10-66

3. HAZARDS IDENTIFICATION

Main hazards Flammable Harmful: may cause lung damage if swallowed. Repeated exposure may

cause skin dryness or cracking.

Other hazards In use, may form flammable/explosive vapour-air mixture.

4. FIRST AID MEASURES

Skin contact Wash off immediately with plenty of soap and water. Remove contaminated clothing.

Eye contact Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek

medical attention.

Inhalation Move the exposed person to fresh air. Seek medical attention.

Ingestion DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water. Seek medical attention.

General information If you feel unwell, seek medical advice (show the label where possible). Keep the

affected person warm and at rest. Remove contaminated clothing. Wash all

contaminated clothing before reuse.

5. FIRE FIGHTING MEASURES

Extinguishing media Use extinguishing media appropriate to the surrounding fire conditions.

Do NOT use ... Water jet.

Protective equipment Wear: Self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Ensure adequate ventilation of the working area. Keep personnel away from spill.

Evacuate personnel to a safe area. Eliminate all sources of ignition.

Environmental precautions Do not allow product to enter drains.

Clean up methods Clean spillage area thoroughly with plenty of water. Absorb with inert, absorbent

material. Transfer to suitable, labelled containers for disposal.

Fiddes Hard Wax Oil

Revision 7

Revision date 20-Jan-2011

7. HANDLING AND STORAGE

Handling Wear suitable protective equipment. Do not breathe gas/fumes/vapour/spray. Use in a

well ventilated area. Vapours are heavier than air. Avoid contact with eyes and skin.

Storage Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures Ensure adequate ventilation of the working area.

Respiratory protection Wear: Suitable respiratory equipment. Self-contained breathing apparatus.

Hand protection Chemical resistant gloves (PVC)

Eye protection Approved safety goggles. Avoid contact with eyes.

Protective equipment Avoid contact with eyes and skin. Adopt best Manual Handling considerations when

handling, carrying and dispensing. Apron (Plastic or rubber) Rubber boots.

9. PHYSICAL AND CHEMICAL PROPERTIES

DescriptionLiquid.ColourAmber.OdourMild.Flash point43°C

Water solubility Soluble in alcohol & ether.

10. STABILITY AND REACTIVITY

Stability Stable under normal conditions.

Conditions to avoid Heat, sparks and open flames.

Materials to avoid Oxidising agents. Acids.

Hazardous decomposition

products

Carbon oxides. Nitrogen oxides.

11. TOXICOLOGICAL INFORMATION

Acute toxicity Headache, nausea and vomiting. In severe cases, may cause loss of consciousness.

Harmful if absorbed through the skin.

Corrosivity May cause irritation to skin.

Repeated or prolonged Prolonged or repeated exposure may cause irritation to skin and mucous membranes.

exposure Repeated or prolonged exposure may cause dermatitis.

12. ECOLOGICAL INFORMATION

Ecotoxicity No data is available on this product.

13. DISPOSAL CONSIDERATIONS

General information Can be incinerated if in compliance with local and national regulations. Dispose of in

compliance with all local and national regulations.

Disposal of packaging Empty containers can be sent for disposal or recycling.

Fiddes Hard Wax Oil

Revision 7

Revision date 20-Jan-2011

14. TRANSPORT INFORMATION

ADR/RID

UN 1263 Packing group III
Class 3 Hazard ID 33

Proper Shipping PAINT.

Name

IMDG

UN 1263 Packing group III Class 3 Marine pollutant .

EmS Code F-E S-E

IATA

UN 1263 Packing group III
Class 3 Subsidiary risk Packing Instruction 310 Maximum quantity 220 L

(Cargo)

Packing Instruction 309 Maximum quantity 60 L

(Passenger)

15. REGULATORY INFORMATION

Labelling The product is classified in accordance with 67/548/EEC.

Symbols Xn - Harmful



Risk phrases R10 - Flammable.

R65 - Harmful: may cause lung damage if swallowed.

R66 - Repeated exposure may cause skin dryness or cracking.

Safety phrases S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show

this container or label.

16. OTHER INFORMATION

Text of risk phrases in R10 - Flammable.

Section 2 R65 - Harmful: may cause lung damage if swallowed.

R66 - Repeated exposure may cause skin dryness or cracking.

Further information The information supplied in this Safety Data Sheet is designed only as guidance for the

safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other

process.

Revision This document differs from the previous version in the following areas:

2 - hazardous ingredients.