SAFETY DATA SHEET



Carl's Oil 45/Bona Oil 45

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance or preparation

Product name : Carl's Oil 45/Bona Oil 45

Product code : Not available.

Synonyms : GT5360

Product description : Not available.

Use of the substance/preparation

Product use : Oil for treatment of wooden floors

None identified.

Company/undertaking identification

Manufacturer : Bona AB

Box 210 74

SE-200 21 MALMÖ

SWEDEN

Tel. +46-(0)40-38 55 00

e-mail address of person

responsible for this SDS

: marie.holmgren@bona.com

2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification according to Regulation (EC) 1907/2006 (REACH)

Classification : R10

R66, R67 R53

Physical/chemical hazards : Flammable.

Human health hazards: Repeated exposure may cause skin dryness or cracking. Vapors may cause

drowsiness and dizziness.

Environmental hazards

: May cause long-term adverse effects in the aquatic environment.

Additional hazards : Risk of self-ignition. Contaminated equipment for cleaning, cloths, rags, dust from

sanding etc. can cause self-ignition. All cloths etc. must be put into water, sealed

containers or be burnt.

Additional warning phrases: Contains 2-Butanone, oxime. May produce an allergic reaction.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC or assigned an occupational exposure limit.

Chemical name	CAS number	%	Number	Classification	
Naphta (petroleum), hydrogen treated heavy	64742-48-9	25 - 50		R10 [1] Xn; R65 R66, R67]
Alkanes, C9-12-iso-	90622-57-4	25 - 50		Xn; R65 [1] R66 R53]
See section 16 for the full text of the R-phrases declared above					

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Date of issue/Date of revision : 2010-07-14. Page: 1/7

3. COMPOSITION/INFORMATION ON INGREDIENTS

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] PBT-substance
- [4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

FIRST AID MEASURES

First aid measures

General

: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use solvents or thinners.

Eye contact

: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.

Ingestion

If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.

FIRE-FIGHTING MEASURES

Extinguishing media

Extinguishing media not to

: Recommended: alcohol-resistant foam, CO₂, powders, water spray.

be used

: Do not use water jet.

Special exposure hazards

: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).

Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Methods for cleaning up

: Preferably clean with a detergent. Avoid using solvents.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

HANDLING AND STORAGE

Handling

: Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.

Date of issue/Date of revision : 2010-07-14.

7. HANDLING AND STORAGE

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see section 8). Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Storage : Store in accordance with local regulations. Observe label precautions. Store in a dry,

cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep away from sources of ignition. Keep away from: oxidizing agents, strong alkalis,

strong acids.

No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not empty into drains.

8. **EXPOSURE CONTROLS/PERSONAL PROTECTION**

Occupational exposure limits

: Not available.

Exposure controls

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

Occupational exposure controls

Respiratory system

: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Skin and body

: Personnel should wear antistatic clothing made of natural fibers or of high-

temperature-resistant synthetic fibers.

Hands

Gloves

: For prolonged or repeated handling, use the following type of gloves:

Recommended: nitrile rubber

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Environmental exposure

controls

: Use safety eyewear designed to protect against splash of liquids.

: Do not allow to enter drains or watercourses.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquid. Color Brown.

Flash point Closed cup: 36°C (96,8°F) Kinematic: 0,09 cm²/s (9 cSt) **Viscosity**

Relative density 0.85

Solubility : Insoluble in the following materials: cold water and hot water.

10. STABILITY AND REACTIVITY

Conditions to avoid

: Stable under recommended storage and handling conditions (see section 7). When exposed to high temperatures may produce hazardous decomposition products.

Materials to avoid

Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Date of issue/Date of revision : 2010-07-14.

11. TOXICOLOGICAL INFORMATION

Toxicokinetics

Absorption: Not available.

Distribution : Contains material which may cause damage to the following organs: lungs, mucous

membranes, digestive system, upper respiratory tract, skin, central nervous system

(CNS), eye, lens or cornea, head, nose/sinuses, stomach, throat.

Metabolism: Not available.Elimination: Not available.

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Contains 2-Butanone, oxime. May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Naphta (petroleum), hydrogen treated heavy	LC50 Inhalation Vapor	Rat	>14 mg/L	4 hours
	LD50 Dermal	Rabbit	>3200 mg/kg	-
	LD50 Oral	Rat	>6400 mg/kg	-
Alkanes, C9-12-iso-	LD50 Dermal	Rat	>3160 mg/kg	-
	LD50 Oral	Rat	>10000 mg/kg	-

Conclusion/Summary : Not available.

Chronic toxicity

Conclusion/Summary: Not available.

Carcinogenicity

Conclusion/Summary: Not available.

Mutagenicity

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

_				
L				

Conclusion/Summary: Not available.

12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself.

Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See sections 3 and 15 for details.

Aquatic ecotoxicity

Conclusion/Summary: Not available.

Ecological information

Persistence/degradability

Conclusion/Summary: Not available.

Date of issue/Date of revision : 2010-07-14. Page: 4/7

12. ECOLOGICAL INFORMATION

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Naphta (petroleum), hydrogen treated heavy	-	-	Readily
Alkanes, C9-12-iso-	-	-	Inherent
	I		

PBT : Not applicable.

vPvB : Not applicable.

13. DISPOSAL CONSIDERATIONS

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

European waste catalogue

(EWC)

: The European Waste Catalogue classification of this product, when disposed of as waste, is: 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances. If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned.

For further information, contact your local waste authority.

Hazardous waste : Yes.

14. TRANSPORT INFORMATION

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Land - road/railway

UN number : 1263
Transport document name : PAINT
Special provision 640 : E
ADR/RID Class : 3
Packing group : III

ADR/RID Label



<u>Sea</u>

UN number : 1263
Proper shipping name : PAINT

Special provisions : Not available.

IMDG Class: 3Packing group: III

IMDG Label



Marine pollutant : No.

Emergency schedules : F-E,S-E

(EmS)

Air

UN number : 1263
Proper shipping name : PAINT

Special provisions: Not available.

ICAO/IATA Classification : 3
Packing group : III

Date of issue/Date of revision : 2010-07-14. Page: 5/7

14. TRANSPORT INFORMATION

ICAO/IATA label



Inland waterways

Proper shipping name Packing group

15. REGULATORY INFORMATION

Chemical Safety Assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

EU regulations

The product is classified and labelled for supply in accordance with the Directive

1999/45/EC as follows:

Risk phrases

: R10- Flammable.

R66- Repeated exposure may cause skin dryness or cracking.

R67- Vapors may cause drowsiness and dizziness.

R53- May cause long-term adverse effects in the aquatic environment.

Safety phrases

: S2- Keep out of the reach of children.

S24- Avoid contact with skin.

S60- This material and its container must be disposed of as hazardous waste. S62- If swallowed, do not induce vomiting: seek medical advice immediately and

show this container or label.

VOC for Ready-for-Use

Mixture

: IIA/f. Interior and exterior minimal build woodstains. EU limit values: 700g/l (2007)

700g/l (2010.)

This product contains a maximum of 450 g/I VOC.

Detergents - Regulation

(EC) No 907/2006

: Not applicable.

Europe inventory

: Not determined.

Other EU regulations

Additional warning phrases: Contains 2-Butanone, oxime. May produce an allergic reaction.

Additional warning phrases: Not applicable.

(CEPE)

The information in this Safety Data Sheet is required pursuant to Annex II to Regulation (EC) No 1907/2006.

16. OTHER INFORMATION

CEPE Classification

Full text of R-phrases referred to in sections 2 and : R10- Flammable.

R65- Harmful: may cause lung damage if swallowed.

R66- Repeated exposure may cause skin dryness or cracking.

R67- Vapors may cause drowsiness and dizziness.

R53- May cause long-term adverse effects in the aquatic environment.

Classification according to **Regulation (EC) 1272/2008**

(CLP)

3 - Europe

: FLAMMABLE LIQUIDS - Category 3

ACUTE TOXICITY: INHALATION - Category 3

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 35,8% Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

aquatic environment: 72,8%

Restrictions on use

None identified.

Date of issue/ Date of

2010-07-14.

revision

Version : 1

Indicates information that has changed from previously issued version.

Notice to reader

Date of issue/Date of revision : 2010-07-14.

16. OTHER INFORMATION

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Annex

Date of issue/Date of revision : 2010-07-14. Page: 7/7

