HC101 Petworth





Product Details

Product Code	HC101				
Collection	Home by V4 Wood Flooring				
Construction	Engineered				
Species	Oak				
Product Type	Engineered Plank				
Surface	Brushed & Stained				
Finish	Matt Lacquered				
Total Thickness	14 mm				
Top Layer	3 mm - Solid European Oak				
Core Layer	11 mm – 2 Layer Softwood				
Grade	CD/ Rustic				
Pack Size	2.888 m²				
Pack Contents	8 Boards - May Include 2 split lengths				
Joint Type	Tongue & Grooved				
Edge Profile	Bevel Edged on 4 sides				

Technical Information

Country of Manufacture	China			
EUTR/ European Timber Regulation	Full documented evidence of legality of timber			
FSC® Certification	Not available with this product			
PEFC® Certification	Not available with this product			
Janka Hardness	Oak 1360 lbf (6000N)			
Slip Resistance	Contact V4 Customer Support			
European Reaction to Fire Classification	EN 13501-1 (test result: Dn - S1)			
Release of Formaldehyde	EN 717-1 (Test result < 0.012mg/m3)			
Thermal Conductivity	Contact V4 Customer Support			
Tog Rating	1.12			

Grading CD/ Rustic

V4 Wood Flooring is chosen for its natural beauty, therefore grading criteria is always an approximation as every piece of timber is different. If further selection is needed please allow for extra material upon installation.

Maximum Size of Sound Knots	50 mm Diameter (approx')			
Maximum Size of Filled Knots	30 mm Diameter (approx')			
Filled Defects	Allowed			
Filler Type	Black and dark brown filler			
Sap Wood	Allowed (few Sapwood at the corner allowed)			
End Checks	Not Allowed			
Heart Wood	Allowed			
Insect Damage	Not Allowed			
Colour Variation	Allowed			
Small Shakes	Allowed			
Ingrown Bark	Not Allowed			
Grain Variation	Allowed			

Installation Methods

All V4 floors should be installed by experienced flooring installers who have read and understood the appropriate installation guides at www.v4woodflooring.co.uk

Fully Bonded	Yes*
Secret Nailed	No
Floated on Underlay	No
Over Underfloor Heating	Yes* (fully bonded installation recommended)

Maintenance Schedule Advice

Avoid scratches by minimising grit and dust, install doorway entrance mats and felt pads to protect furniture. Use PH neutral cleaners and avoid soaking the floor with water. For more detailed advice visit www.v4woodflooring.co.uk

Recommended Products	Initial	Regular	Monthly	Long Term
Sweep/ Vacuum	√	√		
Wood's Good Natural Floor Care Refresher	√		√	
Wood's Good Natural Floor Care		√		
Sanded and Re-lacquered				√



V4 Wood Flooring®

Call +44(0)1276 488099 Email team@v4woodflooring.co.uk Visit www.v4woodflooring.co.uk *Subject to correctly prepared and compatible subfloor and in conjunction with correct installation

© This technical data sheet was written by V4 Wood Flooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.