



## General Description

**Junckers Professional Hardwax Oil** is suitable for sanded and untreated parquet floors.

**Junckers Professional Hardwax Oil** protects the floor and gives the floor a light warm appearance.

**Junckers Professional Hardwax Oil** is used for both priming and finishing. Certain porous timbers may require additional coats to achieved desired result.

## Technical Data

<b>Product:</b>	Hard wax and drying oil in solvents.
<b>Package sizes:</b>	5 litres.
<b>Appearance:</b>	Haze light brown liquid. Dries up to a clear film.
<b>Gloss level:</b>	Matt to Ultramatt.
<b>Coverage:</b>	20-30 m <sup>2</sup> per litre.
<b>Application tools:</b>	Stainless steel spatula, roller or brush. According to gloss a white or red pad for polishing.
<b>Substrate temperature:</b>	Minimum 10°C.
<b>Dilution:</b>	Delivered ready for use.
<b>Drying time:</b>	Dry to touch at least 4 hours at 20°C. Recoating approx. 6 hours at 20°C. Buffing approx. 16 hours at 20°C. Full cure after 6 days at 20°C.
<b>Cleaning of tools:</b>	Soap and water before drying.
<b>Storage:</b>	Lasts for 2 years if unopened and stored at 20°C. Once opened the product will start to form a skin and may harden in the can.

### System Recommendations

- High traffic areas:** 2 coats **Professional Hardwax Oil** 20 m<sup>2</sup>/ltr.  
+ 1 finishing coat **Professional Hardwax Oil** 50 m<sup>2</sup>/ltr.
- Low traffic areas:** 1 coat **Professional Hardwax Oil** 20 m<sup>2</sup>/ltr.  
+ 1 finishing coat **Professional Hardwax Oil** 50 m<sup>2</sup>/ltr.

### Directions for Use

#### Untreated/sanded floors

The surface should be clean, dry and free from dust, wax, grease, polish etc. Machine sand the floor as advised under **Previously treated floors** to remove dirt and irregularities. The last sanding should be carried out by using minimum grit 120 sand screen mesh before applying **Junckers Professional Hardwax Oil**. Thoroughly clean off the sanding dust (e.g. by vacuuming).

Apply **Junckers Professional Hardwax Oil** using suitable tools. Remove surplus material using a buffing machine and a soft cloth or pad. When dry apply subsequent coats as described. To increase gloss, buff using white pad after a minimum 16 hours.

#### Previously treated floors:

Machine sand using grit 24-36. Remove abrasion marks with grit 60-80. Finally, use grit 100-120 to obtain a completely smooth surface. Vacuum sanding dust and coat the floor as described under “**Untreated/ sanded floors**”.

#### Cleaning:

Add **Junckers Sylva Cleaner** to the cleaning water.

#### Maintenance:

Use **Junckers RUSTIC TOP OIL** for refreshing of the surface. For worn surfaces use **Junckers Professional Hardwax Oil** to restore the surface protection.

#### Important!

Wait until full cure before replacing rugs or carpets.

#### Important!

Before use of the product, read the label on the container carefully and observe the advised precautionary safety measures.

#### Important!

Stir well before use.

### Further information

#### Products:

F 2.7 - **Junckers RUSTIC TOP OIL**

F 10.2 - **Junckers Sylva Cleaner**