



## GENERAL DESCRIPTION

Junckers Rustic Oil, Clear is an indoor priming and finishing oil product for untreated wooden floors and table-/worktops.

Junckers Rustic Oil, Clear can be used in combination with Rustic Oil, Colour.

## PRODUCT DESCRIPTION

**Product:** Hardening urethane oil in paraffinic solvent.

**Package sizes:** 0.75 litre, 2.5 litres, 5 litres, 10 litres, 25 litres and 200 litres.

**Appearance:** Provides the wood with a deep, warm glow.

## TECHNICAL DATA

**Coverage:** 10-50 m<sup>2</sup> depending on wood structure and absorption.

**Application tools:**

Cloth, brush, roller, lambswool applicator or spray in combination with a nylon scouring pad for alle types of surfaces.

For floors a buffing machine mounted with a cloth covered pad helps spreading and removal of surplus liquid.

**Substrate temperature:** Minimum 15° C.

**Dilution:** Delivered ready for use. Dilution is not recommended.

**Drying time at 20° C.**

16-24 hours before applying the finishing oil.

Ready for use 24 hours after the finishing treatment.

Fully cured after 3 days.

Do not cover the surface by i.e. carpets or rugs before the oil is fully cured.

**Cleaning of tools:** White spirit.

**Storage:** Lasts for 2 years if unopened and stored at 20°C. Once opened the oil will start to form a skin and may harden in the can.

## SYSTEM RECOMMENDATIONS

### Floors, High traffic:

2 coats of Junckers Rustic Oil clear + 1 coat of Junckers Rustic Oil clear or 2 coats of Junckers HP High Performance.

### Floors, Low traffic:

2 coats of Junckers Rustic Oil clear + 1 coat of Junckers Rustic Oil clear or 2 coats of Junckers ProFinish.

### Table-/worktops:

2 coats of Junckers Rustic Oil clear + 2 thin coats of Junckers Rustic Oil clear.

## DIRECTION FOR USE

### Priming of untreated/sanded wood:

Ensure that the surface is absolutely clean, dry and free from dust, wax, grease, polish etc. Unevenness, dirt and discolouration can be removed by sanding in the direction of the grain. Final sanding must be with sandpaper grit 100-120. Vacuum sanding dust.

Larger areas are recommended to be divided into smaller areas that can be oiled in 30 minutes. Keep any overlaps with dry areas to a minimum.

Stir the oil well before use and prime with 2 coats of Junckers Rustic Oil clear applied wet in wet: Apply one coat of oil and wait up to 30 minutes before applying the second coat. Work the oil for another 30 minutes. Wipe off excess oil. Dried and unabsorbed oil leaves glossy spots on the surface. The surface should appear matt and even.

Leave to dry for 16-24 hours.

### Finishing with Rustic Oil Clear:

Sand or scour the surface carefully with fine sandpaper grit 180-220 or a green or black nylon pad. Vacuum sanding dust.

On floors, apply 1 coat of Junckers Rustic oil. On table-/worktops, apply 2 thin coats of Junckers Rustic oil clear.

Make sure that the surface is saturated and remove surplus oil within 30 minutes with a dry soft cloth and buff the surface to an even finish using a clean cloth under the buffing pad. On floors a buffing machine can be used as well.

### Finishing with lacquer - Floors:

Higher wearability of the floor can be obtained by finishing with lacquer. Choose one of Junckers lacquers according to the recommended systems.

Please note, that its very important the floor is a 100 % saturated with oil before lacquering. If not, there is a risk of discoloration and especially oak may need extra oil.

Screen with a black pad and remove the dust. Apply one coat of lacquer and leave to dry approx. 4 hours.

Apply the final coat of lacquer and leave to dry until fully cured.

### Care and maintenance, lacquered floors:

If the surface is worn through the floor must be sanded and the area must be re-treated with oil and lacquer.

**Care and maintenance, oiled surfaces:**

If the existing oil surface is sound and stable the floor can be maintained with Junckers water based Rustic Top Oil.

On floors and table-/worktops, refresh with Junckers Rustic Oil clear, if the surface shows sign of wear. Method as described under "Finishing with Rustic Oil clear".

**IMPORTANT!**

Before using the product, read the label on the container carefully and observe the recommended precautionary measures. See Material Safety Data Sheet for detailed information about precautionary measures.

**FURTHER INFORMATION**

**Products:**

F 4.2 - Junckers ProFinish

F 2.7 - Junckers Rustic Top Oil

F 8.5 - Junckers HP Commercial