



General Description

Junckers Rustic Oil colour is an oil product for staining of untreated table tops, and wooden floors.

Technical Data

Product:	Coloured drying urethane oil in low odor solvent.
Package sizes:	0.75 litre, 2.5 litre and 5 litre.
Appearance:	Coloured liquid that dries to a transparent coloured surface.
Colours:	White Black Anthracite grey/SpicyPepper DarkCoco Mahogany/SylvaRed Nut/SylvaKet RawSugar SmoothRum Walnut WildHazel Cherry
Coverage:	Oil-treated or impregnated wood: 20-50 m ² per litre. Untreated wood: 5-10 m ² per litre.
Application tools:	All surfaces: Cloth, brush, Roller or lambswool applicator in combination with a nylon scouring pad. Floors: A buffing machine mounted with a cloth covered pad, helps spreading and removal of surplus liquid.
Substrate temperature:	Minimum 5°C.
Dilution:	Delivered ready for use. Dilution is not recommended.
Drying time:	12-16 hours before applying the finishing oil. 16-24 hours before applying the finishing lacquer. Ready for use 24 hours after the finishing treatment. Fully cured after 3 days. Do not cover the surface by i.e. carpets or rugs before the oil is fully cured.
Cleaning of tools:	White spirit.
Storage:	2 years if unopened and stored at 20°C. Once opened the oil will start to form a skin and may harden in the can.

System Recommendations

Floors and table tops: 1+1 coat **Junckers Rustic Oil colour**
+ 1-2 coats **Junckers Rustic Oil clear** or colour

Floors (finishing with lacquer):
High traffic areas: 1+1 coat **Junckers Rustic Oil colour**
+ 2 coats **Junckers High Performance Commercial**.

Low traffic areas: 1+1 coat **Junckers Rustic Oil colour**
+ 2 coats **Junckers ProFinish**

Directions for Use

Staining of untreated/sanded wood:

- 1) Ensure that the surface is absolutely clean, dry and free from dust, wax, grease, polish etc. Unevenness, dirt and discolouration can be removed by sanding in the direction of the grain. Final sanding must be with sandpaper grit 100-120. Vacuum sanding dust.
- 2) Moisten the surface with a damp cloth. Be sure that the floor is evenly and visibly wetted to avoid a patchy appearance of the staining. Then leave to dry 10-15 minutes.
- 3) Prime with 2 coats of **Junckers Rustic Oil colour** applied wet in wet: Apply one coat of oil and wait up to 30 minutes before applying the second coat. Work the oil for another 30 minutes. Wipe off excess oil. NB: Dried and unabsorbed oil leaves glossy spots on the surface. The surface should appear matt and even. Larger areas are recommended to be divided into smaller areas of 10-25 m². Always keep a wet edge between areas.

Finishing with Junckers Rustic Oil clear or colour:

- 1) Screen with a black pad and remove the dust.
 - 2) Depending on colour intensity, finish with either clear or coloured oil.
- The surface is protected by **Junckers Rustic Oil clear** or colour by applying 1-2 thin coats followed by drying, all according to the recommendations. Polish until an even appearance is obtained.

Finishing with lacquer - Floors:

Higher wearability of the floor can be obtained by finishing with lacquer. Choose one of Junckers lacquers according to the recommended systems.

- 1) Screen with a black pad and remove the dust.
- 2) Apply one coat of lacquer. Leave to dry 24 hours.
- 3) Sand with 180-220 grit sandpaper. Vacuum sanding dust. Remove sanding dust with a vacuum cleaner and wipe away with a damp cloth.
- 4) Apply the final coat of lacquer. Leave to dry until fully cured.

Cleaning and maintenance – oiled surfaces:

Use **Junckers Rustic Oil clear** or colour as surface refresher if any sign of wear appear. Maintain with **Junckers Rustic Top Oil**.

Oiled surfaces worn through:

Sanding to untreated wood of the full area, followed by a new application of stain and finish is necessary to obtain an even appearance.

Important!

Before use of the product, read the label on the container carefully and observe the advised precautionary safety measures.

Important!

Stir well before use.

Important!

All spillages on worktops/floors must be wiped off immediately, as the surface is generally flat and provides no run off. If liquid/spillage remains in situ then it may cause watermarking/water damage.

Important!

The treated surface must be refinished / rejuvenated as and when required.

Further information

Products:

- F 2.1 - **Junckers Rustic Oil clear**
- F 2.7 - **Junckers Rustic Top Oil**
- F.4.2 - **Junckers ProFinish**
- F 8.5 - **Junckers High Performance Commercial**