CE DECLARATION OF PERFORMANCE			
1.	Unique identification code of the product-type:		
	Multi-layer Parquet / EN 14342 / 12,5 mm (HDF core) - 14 mm (Spruce core)		
2.	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):		
	Quick-Step: Cadenza - Compact - Imperio - Castello - Villa - Palazzo - Variano - Massimo		
3.	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specifi- cation, as foreseen by the manufacturer:		
	For use as floor covering in buildings (see EN 14342) according to the manufacturer's specifications.		
4.	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):		
	Unilin, division Flooring, Ooigemstraat 3 - B-8710 Wielsbeke, Belgium		
5.	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):		
	not applicable		
6.	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:		
	System 3		
7.	In case of the declaration of performance concerning a construction product covered by a harmonised standard: Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).		
	EPH - Dresden - Germany, CWFT not applicable		
	Notified Body certificate of constancy of performance		
8.	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: not applicable		
9.	Declared performance Essential characteristics	Performance	Harmonised technical specification
	Reaction to fire	12,5 mm: 14 mm	EN 14342: 2005+A1 2008
	Content of Pentachlorophenol	Ů DL PCP	EN 14342: 2005+A1 2008
	Formaldehyd Emissions	° Е1 НСНО	EN 14342: 2005+A1 2008
	Slip resistance	USRV 48 - 52	EN 14342: 2005+A1 2008
	Biological Durability	Class 1	EN 14342: 2005+A1 2008
	Thermal conductivity [W/mK]	R: 12,5 mm = 0,110 m² K/W - 14 mm = 0,140 m² K/W	EN 14342: 2005+A1 2008
10.	The performance of the product identified in points 1 and 2 This declaration of performance is issued under the sole res Signed for and on behalf of the manufacturer by: Jasper De Jaeger, technical services manager	t 9.	
	(name and function) Wielsbeke, 11/05/2016		
	(place and date of issue)		(signature)