

Safety Data Sheet

according to 1907/2006/EC, Article 31

Page 1/7

Printing date 08.02.2008

Revision: 08.02.2008

Product details		
Trade name: Application of the substance /	Osmo Wood Wax Finish Transparent	
preparation	Coating compound/ Surface coating/ paint	
Manufacturer/Supplier:	Osmo Holz und Color GmbH & Co. KG Affhüppen Esch 12 D-48231 Warendorf	
Further information obtainab		
from:	Product safety department Phone: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462	
	e-mail: helmut.starp@osmo.de	
Information in case of emergency:	emergency phone no. Berlin (24h): +49 (0) 30 / 19240	
Hazards identification		
Hazard description:	Not applicable.	
Information concerning		
particular hazards for human		
environment: Classification system:	The product does not have to be labelled due to the calculation procedure of t "General Classification guideline for preparations of the EU" in the latest valid version The classification is according to the latest editions of the EU-lists, and extended company and literature data.	
Composition/information	ı on ingredients	
Chemical characterization		
Description:	Mixture of substances listed below with nonhazardous additions.	
Dangerous components:		
CAS: 64742-48-9 Naphtha EINECS: 265-150-3	(petroleum), hydrotreated heavy Xn; R 65-66 25-50	
	For the wording of the listed risk phrases refer to section 16.	
Additional information:		
-		
First aid measures	Immediately remove any clothing soiled by the product	
	Immediately remove any clothing soiled by the product. Supply fresh air. If required, provide artificial respiration. Keep patient warm. Cons doctor if symptoms persist.	
First aid measures General information:	Supply fresh air. If required, provide artificial respiration. Keep patient warm. Cons	



Page 2/7

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.02.2008

Revision: 08.02.2008

	ade name: Osmo Wood Wax Finish Transparent		
After swallowing:	(Contd. of page If swallowed, seek medical advice immediately and show this container or label.		
Fire-fighting measures			
Suitable extinguishing agents:	CO2, powder or water spray. Fight larger fires with water spray or alcohol resistationam.		
For safety reasons unsuitable			
extinguishing agents:	Water with full jet		
Special hazards caused by the			
substance, its products of			
combustion or resulting gases:	Formation of toxic gases is possible during heating or in case of fire.		
Protective equipment:	Mouth respiratory protective device.		
Additional information	Cool endangered receptacles with water spray.		
	Dispose of fire debris and contaminated fire fighting water in accordance with offic regulations.		
6 Accidental release measures			
Person-related safety precautions:			
	Ensure adequate ventilation		
Measures for environmental			
protection:	Do not allow to enter sewers/ surface or ground water.		
	Inform respective authorities in case of seepage into water course or sewage system.		
Measures for cleaning/collecting:	Warm water and cleansing agent Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders sawdust).		
7 Handling and storage			
Handling:			
Information for safe handling:	Keep receptacles tightly sealed.		
	Keep away from heat and direct sunlight.		
	Use only in well ventilated areas.		
	Prevent formation of aerosols.		
Information about fire - and			
explosion protection:	Keep ignition sources away - Do not smoke.		
Storage:			
Requirements to be met by			
storerooms and receptacles:	Store in a cool location.		
storerooms and receptactes:	Store only in the original receptacle.		
Information about storage in one	Store only in the original receptacie.		
common storage facility:	Do not store together with alkalis (caustic solutions).		



Page 3/7

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.02.2008

Revision: 08.02.2008

GB

	(Contd of nor
	(Contd. of pag Do not store together with oxidizing and acidic materials.
Further information about	
storage conditions:	Keep container tightly sealed.
0	Store receptacle in a well ventilated area.
	Protect from frost.
	Protect from heat and direct sunlight.
Exposure controls/person	al protection
Additional information about	
design of technical facilities:	No further data; see item 7.
Ingredients with limit values the	at require monitoring at the workplace:
-	m), hydrotreated heavy (25-50%)
TWA (8H) Short-term value: 10	
Source UK SIA	
Additional information:	The lists valid during the making were used as basis.
Personal protective equipment:	
General protective and hygienic	
measures:	Immediately remove all soiled and contaminated clothing
	Avoid contact with the eyes and skin.
	Do not eat, drink, smoke or sniff while working.
	Do not carry product impregnated cleaning cloths in trouser pockets.
Protection of hands:	Protective gloves
	The glove material has to be impermeable and resistant to the product/ the substar
	the preparation.
	Selection of the glove material on consideration of the penetration times, rates
	diffusion and the degradation
Material of gloves	Nitrile rubber, NBR
Penetration time of glove mater	<i>ial</i> The exact break trough time has to be found out by the manufacturer of the protect
	gloves and has to be observed.
For the permanent contact glow	
made of the following materials	
are suitable:	Nitrile rubber, NBR
As protection from splashes	
gloves made of the following materials are suitable:	Nitrile rubber NPP
maieriais are sulladie:	Nitrile rubber, NBR
Eye protection:	Goggles recommended during refilling



Page 4/7

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.02.2008

Trade name: Osmo Wood Wax Finish Transparent (Contd. of page 3) 9 Physical and chemical properties **General Information** Form: Fluid According to product specification Colour: **Odour:** Mild Change in condition Melting point/Melting range: Undetermined. >180°C (DIN 51751) **Boiling point/Boiling range:** Flash point: 57°C (DIN 52231) 240°C Ignition temperature: Product is not selfigniting. Self-igniting: Danger of explosion: Product does not present an explosion hazard. **Explosion limits:** Lower: 0.6 Vol % 7.0 Vol % Upper: Vapour pressure: 3 hPa [20°C] Density at 20°C: 0.90 - 0.96 g/cm3 (DIN 51757) Solubility in / Miscibility with Not miscible or difficult to mix. water: Viscosity: Kinematic at 20°C: >81 s (DIN 53211/4) Solvent content: VOC (EC) < 400 g/l (VOC-max. = 400 g/l (2010 A/e))10 Stability and reactivity

Thermal decomposition /					
conditions to be avoided:	No decomposition if used and stored according to specifications.				
angerous reactions Reacts with fabric soaked in the product (e.g. cleaning wool).					
	Exothermic reaction.				
	Forms heat.				
	Self igniting.				
	Reacts with acids, alkalis and oxidizing agents.				
Dangerous decomposition					
products:	Carbon monoxide and carbon dioxide				
	Nitrogen oxides (NOx)				
			(G)	. 1	~ ``

Revision: 08.02.2008



Page 5/7

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.02.2008

Revision: 08.02.2008

GB

64742-48-9 Oral Dermal Inhalative 96-29-7 2-1	gical info city: calues relev D Naphtha LD50 LD50 LC50/4 h	warning: Wash out any used cloth impregnated with this product immedeately after use or st in an airtight container (danger of self-ingnition). permation permation permation: (petroleum), hydrotreated heavy >2000 mg/kg (rat) >2000 mg/kg (rat)
Acute toxic LD/LC50 v 64742-48-9 Oral Dermal Inhalative 96-29-7 2-1	zity: palues relev P Naphtha LD50 LD50 LC50/4 h	in an airtight container (danger of self-ingnition).
Acute toxic LD/LC50 v 64742-48-9 Oral Dermal Inhalative 96-29-7 2-1	zity: palues relev P Naphtha LD50 LD50 LC50/4 h	vant for classification: (petroleum), hydrotreated heavy >2000 mg/kg (rat) >2000 mg/kg (rat)
Acute toxic LD/LC50 v 64742-48-9 Oral Dermal Inhalative 96-29-7 2-1	zity: palues relev P Naphtha LD50 LD50 LC50/4 h	vant for classification: (petroleum), hydrotreated heavy >2000 mg/kg (rat) >2000 mg/kg (rat)
LD/LC50 64742-48-9 Oral Dermal Inhalative 96-29-7 L	Palues relev Naphtha LD50 LD50 LC50/4 h	(petroleum), hydrotreated heavy >2000 mg/kg (rat) >2000 mg/kg (rat)
64742-48-9 Oral Dermal Inhalative 96-29-7 2-4	9 Naphtha LD50 LD50 LC50/4 h	(petroleum), hydrotreated heavy >2000 mg/kg (rat) >2000 mg/kg (rat)
Oral] Dermal] Inhalative] 96-29-7 2-1	LD50 LD50 LC50/4 h	>2000 mg/kg (rat) >2000 mg/kg (rat)
Dermal I Inhalative 96-29-7 2-t	LD50 LC50/4 h	>2000 mg/kg (rat)
Inhalative	LC50/4 h	
96-29-7 2-t		
	hutenone	>5 mg/l (rat)
Oral	ouranone	oxime
	LD50	3700 mg/kg (rat)
Dermal	LD50	200-2000 mg/kg (rat)
Inhalative		20 mg/l (rat)
Primary irr	ritant effec	<i>t:</i>
on the skin	:	At long or repeated contact with skin it may cause dermatitis due to the degreas
_		effect of the solvent.
on the eye:		Irritating effect.
Sensitizatio Additional		No sensitizing effects known.
information		The product is not subject to classification according to the calculation method of General EU Classification Guidelines for Preparations as issued in the latest version When used and handled according to specifications, the product does not have harmful effects to our experience and the information provided to us. Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia- conditions and headache, dizziness, etc.
Ecologico General no	U	
General no	nes:	Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous water
		Do not allow product to reach ground water, water course or sewage system.



Page 6/7

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.02.2008

Revision: 08.02.2008

(Contd. of page 5)

Trade name: Osmo Wood Wax Finish Transparent

13 Disposal considerations

Product:

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European	waste	catalogue	

08 01 11 waste paint and varnish containing organic solvents or other dangerous substances

15 01 10 packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging: Recommendation:

Disposal must be made according to official regulations.

14 Transport information

Land transport ADR/RID (c		
ADR/RID class:	3 Flammable liquids.	
Danger code (Kemler):	30	
UN-Number:	1263	
Packaging group:	III	
Hazard label:	3	
Description of goods:	1263 PAINT	
Maritime transport IMDG:		
IMDG Class:	3	
UN Number:	1263	
Label	3	
Packaging group:	III	
EMS Number:	F-E,S-E	
Marine pollutant:	No	
Proper shipping name:	PAINT	
Air transport ICAO-TI and L	ATA-DGR:	
ICAO/IATA Class:	3	
UN/ID Number:	1263	
Label	3	
Packaging group:	III	
Proper shipping name:	PAINT	

GB -



Revision: 08.02.2008

Page 7/7

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.02.2008

Department issuing MSDS:

Contact:

	(Contd. of pag
Regulatory information	n
Labelling according to EU	
guidelines:	The product is not subject to identification regulations under EU Directives and Ordinance on Hazardous Materials (German GefStoffV). Although this product is not subject to identification regulations, we recommend the safety suggestions are observed.
Safety phrases:	 Keep out of the reach of children. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and s medical advice. If swallowed, seek medical advice immediately and show this container or lab Use only in well-ventilated areas.
Special labelling of certain	
preparations:	Warning: Wash out any used cloth impregnated with this product immedeately after use or st in an airtight container (danger of self-ingnition). Contains 2-butanone oxime. May produce an allergic reaction. Safety data sheet available for professional user on request.
National regulations:	
VOC (EC)	< 400 g/l (VOC-max. = 400 g/l (2010 A/e))
Other information	
	n our present knowledge. However, this shall not constitute a guarantee for any specific products a legally valid contractual relationship.

product safety department

Hr. Dr. Starp